

屋内照明器具特性

品番 (品名)	L S E W5 0 3 0									
光源	LED2700_70_370 ×1					370.0 l m				
管理番号	K0160148 (0) DB 1									
B Z 分類	B Z 3									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %			
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30		10		
上方光束	0 %	反射率	床	10 %				10 %				10 %				10 %				0 %		
下方光束	100 %		室指数	照明率 (X0.01)																		
保守率	良	0.67	0.6	63	52	45	40	62	51	45	40	59	50	44	40	57	49	44	40	38		
	中	0.63	0.8	73	64	57	52	72	63	57	52	70	62	56	52	67	60	55	51	50		
	否	0.56	1.0	80	71	65	60	79	71	65	60	76	69	64	60	74	68	63	59	57		
			1.25	86	78	72	68	84	77	72	68	82	76	71	67	79	74	70	67	65		
下方投影面積	c m ²		1.5	90	83	77	73	88	82	77	73	86	80	76	72	83	79	75	72	70		
	等価発光面積		2.0	94	89	84	81	93	88	84	80	90	86	82	79	88	84	81	78	76		
取付高さ	器具間隔最大限		2.5	97	93	89	85	96	92	88	85	93	90	87	84	91	88	85	83	81		
	横方向 (A)	縦方向 (B)	3.0	99	95	92	89	98	94	91	88	95	92	89	87	93	90	88	86	84		
H m	1.19 H m	1.19 H m	4.0	101	98	96	93	100	97	95	92	98	95	93	91	95	93	92	90	87		
			5.0	103	100	98	96	102	99	97	95	99	97	95	94	97	95	94	92	90		
			7.0	104	103	101	99	103	101	100	98	101	99	98	97	99	97	96	95	92		
			10.0	106	104	103	102	104	103	102	101	102	101	100	99	100	99	98	97	95		

