

屋内照明器具特性	
品番 (品名)	L G D 9 1 0 3
光源	L L D 3 0 2 0 C U 1 × 1 6 1 5 . 0 l m
管理番号	K 0 1 7 9 0 1 3 (0) D R 1
B Z 分類	B Z 1

器具効率	93 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
			床	10 %				10 %				10 %				10 %				0 %				
上方光束	0 %	室指数	照明率 (X0.01)																		ZCM			
下方光束	93 %																							
保守率	良	0.67	0.6	78	72	69	66	77	72	68	66	76	71	68	66	75	71	68	66	65				
	中	0.63	0.8	83	78	75	72	82	78	74	72	81	77	74	72	80	76	73	71	70				
	否	0.56	1.0	86	82	78	76	85	81	78	76	84	80	78	75	82	79	77	75	74				
			1.25	89	85	82	80	88	84	82	79	87	83	81	79	85	82	80	78	77				
下方投影面積	cm ²		1.5	91	87	85	82	90	87	84	82	88	86	83	81	87	84	82	81	79				
等価発光面積	cm ²		2.0	93	90	88	86	92	90	87	86	91	88	86	85	89	87	85	84	82				
取付 高さ	器具間隔最大限		2.5	95	92	90	88	94	91	90	88	92	90	88	87	90	89	87	86	84				
	横方向 (A)	縦方向 (B)	3.0	96	94	92	90	95	93	91	90	93	91	90	88	91	90	89	87	86				
Hm	0.36Hm	0.36Hm	4.0	97	95	94	92	96	94	93	92	94	93	92	90	92	91	90	89	87				
			5.0	98	96	95	94	97	95	94	93	95	94	93	92	93	92	91	90	88				
			7.0	98	97	96	96	97	96	96	95	95	95	94	93	93	93	92	92	89				
			10.0	99	98	98	97	98	97	97	96	96	95	95	94	94	93	93	93	90				

