

屋内照明器具特性	
品番 (品名)	L G D 9 1 0 3
光源	LLD40402CQ1 (KAKUSAN) ×1 860.0 l m
管理番号	K0184509 (0) DR 1
B Z 分類	B Z 3

器具効率		79 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) Z C M																				
保守率		良 中 否	0.67	0.6	49	40	35	31	48	40	35	31	46	39	34	31	45	38	34	31	29				
			0.63	0.8	57	49	44	40	56	49	44	40	54	48	43	40	52	47	43	39	38				
			0.56	1.0	62	55	50	46	61	55	50	46	59	53	49	46	57	52	49	45	44				
				1.25	67	60	56	52	66	60	55	52	64	59	55	51	62	57	54	51	49				
下方投影面積		cm ²	1.5	70	64	60	56	69	63	59	56	67	62	58	55	65	61	58	55	53					
			2.0	74	69	65	62	73	68	65	62	70	67	64	61	69	65	63	60	59					
等価発光面積		cm ²	2.5	76	72	69	66	75	71	68	66	73	70	67	65	71	68	66	64	62					
			3.0	78	74	71	69	77	73	71	68	75	72	70	67	73	70	68	67	65					
H m	1.23 H m	1.23 H m	4.0	80	77	75	73	79	76	74	72	77	75	73	71	75	73	71	70	68					
			5.0	81	79	77	75	80	78	76	74	78	76	75	73	76	75	73	72	70					
			7.0	82	81	79	78	81	80	78	77	79	78	77	76	77	76	75	74	72					
			10.0	83	82	81	80	82	81	80	79	80	79	79	78	79	78	77	76	74					

