

屋内照明器具特性	
品番 (品名)	L G D 9 1 0 5
光源	L L D 4 0 0 0 L C E 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 7 5 4 9 7 (0) D R 1
B Z 分類	B Z 3

器具効率		8 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
						照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	5 0	4 1	3 5	3 1	4 9	4 1	3 5	3 1	4 7	4 0	3 5	3 1	4 6	3 9	3 4	3 1	3 0	
			0 . 6 3	0 . 8	5 8	5 0	4 5	4 1	5 7	5 0	4 5	4 1	5 5	4 9	4 4	4 1	5 4	4 8	4 4	4 0	3 9	
			0 . 5 6	1 . 0	6 4	5 7	5 1	4 7	6 3	5 6	5 1	4 7	6 1	5 5	5 0	4 7	5 9	5 4	5 0	4 7	4 5	
				1 . 2 5	6 8	6 2	5 7	5 4	6 7	6 1	5 7	5 3	6 5	6 0	5 6	5 3	6 3	5 9	5 5	5 3	5 1	
下方投影面積		c m ²	1 . 5	7 1	6 6	6 1	5 8	7 0	6 5	6 1	5 7	6 8	6 4	6 0	5 7	6 6	6 2	5 9	5 7	5 5		
			等価発光面積	2 . 0	7 5	7 1	6 7	6 4	7 4	7 0	6 6	6 3	7 2	6 8	6 5	6 3	7 0	6 7	6 4	6 2	6 0	
取付高さ	器具間隔最大限		2 . 5	7 8	7 4	7 1	6 8	7 7	7 3	7 0	6 7	7 4	7 1	6 9	6 7	7 3	7 0	6 8	6 6	6 4		
	横方向 (A) 縦方向 (B)		3 . 0	7 9	7 6	7 3	7 1	7 8	7 5	7 2	7 0	7 6	7 4	7 1	6 9	7 4	7 2	7 0	6 8	6 6		
H m	1 . 2 4 H m	1 . 2 4 H m	4 . 0	8 1	7 9	7 6	7 4	8 0	7 8	7 6	7 4	7 8	7 6	7 4	7 3	7 6	7 5	7 3	7 2	7 0		
			5 . 0	8 2	8 0	7 8	7 7	8 1	7 9	7 8	7 6	7 9	7 8	7 6	7 5	7 8	7 6	7 5	7 4	7 2		
			7 . 0	8 4	8 2	8 1	7 9	8 3	8 1	8 0	7 9	8 1	8 0	7 8	7 7	7 9	7 8	7 7	7 6	7 4		
			1 0 . 0	8 5	8 4	8 3	8 2	8 4	8 3	8 2	8 1	8 2	8 1	8 0	7 9	8 0	7 9	7 9	7 8	7 6		

