

屋内照明器具特性	
品番 (品名)	L G D 9 2 0 1
光源	L L D 5 0 2 0 L C C 1 × 1 1 0 8 5 . 0 l m
管理番号	K 0 1 9 0 3 8 0 (0) D R 1
B Z 分類	B Z 1

器具効率		99 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束		0 %	室指数	照明率 (X0.01)																		Z C M
下方光束		99 %																				
保守率		良 中 否	0.67	0.6	77	70	65	62	76	69	65	62	75	69	65	62	73	68	64	61	60	
			0.63	0.8	84	77	72	69	83	76	72	69	81	75	72	69	79	74	71	68	67	
			0.56	1.0	88	82	77	74	87	81	77	74	85	80	76	73	83	79	76	73	71	
				1.25	91	86	82	79	90	85	81	78	88	84	80	78	86	83	80	77	76	
下方投影面積		c m ²		1.5	94	89	85	82	93	88	85	82	91	87	84	81	89	85	83	80	79	
				2.0	97	93	90	87	96	92	89	86	94	90	88	86	92	89	87	85	83	
取付 高さ	器具間隔最大限			2.5	99	96	93	90	98	95	92	90	96	93	91	89	93	91	89	88	85	
	横方向 (A)	縦方向 (B)		3.0	100	97	95	93	99	96	94	92	97	95	93	91	95	93	91	90	87	
H m	0.41 H m	0.41 H m		4.0	102	100	98	96	101	99	97	95	99	97	95	94	96	95	94	92	90	
				5.0	103	101	99	98	102	100	99	97	100	98	97	96	97	96	95	94	91	
				7.0	104	103	102	100	103	102	101	99	101	100	99	98	99	98	97	96	93	
				10.0	105	104	103	102	104	103	102	101	102	101	100	99	99	98	98	95		

