

屋内照明器具特性	
品番 (品名)	L G D 9 4 0 0
光源	L L D 3 0 2 0 L C E 1 × 1 7 9 5 . 0 l m
管理番号	K 0 1 7 5 5 5 9 (0) D R 1
B Z 分類	B Z 1

器具効率		88 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
					床	10 %				10 %				10 %				10 %				0 %		
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M	
下方光束		88 %																						
保守率		良	0 . 6 7	0 . 6	73	67	63	61	72	67	63	61	71	66	63	61	70	66	63	61	60			
		中	0 . 6 3	0 . 8	78	73	69	67	77	72	69	67	76	72	69	66	74	71	68	66	65			
		否	0 . 5 6	1 . 0	81	76	73	71	80	76	73	71	79	75	72	70	77	74	72	70	69			
				1 . 2 5	84	80	77	74	83	79	76	74	81	78	76	74	80	77	75	73	72			
下方投影面積		c m ²		1 . 5	86	82	79	77	85	81	79	77	83	80	78	76	81	79	77	75	74			
等価発光面積		c m ²		2 . 0	88	85	83	80	87	84	82	80	85	83	81	79	84	82	80	79	77			
取付高さ	器具間隔最大限			2 . 5	89	87	85	83	88	86	84	82	87	85	83	82	85	83	82	81	79			
	横方向 (A)		縦方向 (B)	3 . 0	90	88	86	85	89	87	86	84	88	86	84	83	86	84	83	82	80			
H m	0 . 4 1 H m		0 . 4 1 H m	4 . 0	92	90	88	87	91	89	88	86	89	87	86	85	87	86	85	84	82			
				5 . 0	92	91	90	88	91	90	89	88	89	88	87	86	88	87	86	85	83			
				7 . 0	93	92	91	90	92	91	90	89	90	89	89	88	88	88	87	87	84			
				10 . 0	94	93	92	92	93	92	91	91	91	90	90	89	89	89	88	88	85			

