

屋内照明器具特性	
品番 (品名)	L G D 9 4 0 1
光源	LLD40402CQ1 (KAKUSAN) ×1 860.0 l m
管理番号	K0184652 (0) DR 1
B Z 分類	BZ5 / 0.7 / BZ4

器具効率		73 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.67	0.6	42	34	28	24	41	33	28	24	40	32	28	24	38	32	27	24	22
			0.63	0.8	50	42	36	32	49	41	36	32	47	40	35	32	45	39	35	32	30
			0.56	1.0	55	47	42	38	54	47	41	38	52	45	41	37	50	44	40	37	35
				1.25	59	52	47	43	58	52	47	43	56	50	46	43	54	49	45	42	41
下方投影面積 等価発光面積		c m ² c m ²		1.5	62	56	51	47	61	55	51	47	59	54	50	47	57	53	49	46	45
				2.0	66	61	57	53	65	60	56	53	63	59	55	53	61	57	54	52	50
				2.5	69	64	61	58	68	64	60	57	65	62	59	56	63	61	58	56	54
				3.0	70	67	63	61	69	66	63	60	67	64	62	59	65	63	61	59	57
H m	1.24 H m	1.24 H m		4.0	73	70	67	65	72	69	66	64	69	67	65	63	68	66	64	62	60
				5.0	74	71	69	67	73	71	69	67	71	69	67	66	69	67	66	65	63
				7.0	75	74	72	70	74	73	71	70	73	71	70	69	71	70	68	67	65
				10.0	77	75	74	73	76	74	73	72	74	73	72	71	72	71	70	70	68

