

屋内照明器具特性	
品番 (品名)	L G D 9 4 0 4
光源	L L D 2 0 0 0 L C E 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 7 5 5 3 5 (0) D R 1
B Z 分類	B Z 4 / 1 . 4 / B Z 3

器具効率		85 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
上方光束		0 %		床	10 %				10 %				10 %				10 %				0 %		
下方光束		85 %		室指数	照明率 (X 0 . 0 1)																		Z C M
保守率		良 中 否	0 . 6 7	0 . 6	51	41	35	30	50	40	34	30	48	40	34	30	46	39	34	30	28		
			0 . 6 3	0 . 8	60	51	44	40	58	50	44	40	56	49	44	40	54	48	43	39	38		
				1 . 0	65	57	51	47	64	56	51	47	62	55	50	46	60	54	50	46	44		
			0 . 5 6	1 . 2 5	70	63	58	53	69	62	57	53	67	61	56	53	65	60	56	52	51		
下方投影面積		c m ²		1 . 5	74	67	62	58	72	66	62	58	70	65	61	57	68	64	60	57	55		
等価発光面積		c m ²		2 . 0	78	73	69	65	77	72	68	65	75	70	67	64	72	69	66	63	61		
取付 高さ	器具間隔最大限			2 . 5	81	76	73	69	80	76	72	69	77	74	71	68	75	72	70	67	65		
	横方向 (A) 縦方向 (B)			3 . 0	83	79	76	73	82	78	75	72	79	76	74	71	77	75	72	70	68		
H m	1 . 2 5 H m	1 . 2 5 H m		4 . 0	85	82	79	77	84	81	79	76	82	79	77	75	80	78	76	74	72		
				5 . 0	86	84	82	80	85	83	81	79	83	81	79	78	81	79	78	77	74		
				7 . 0	88	86	84	83	87	85	84	82	85	83	82	81	83	81	80	79	77		
				10 . 0	89	88	87	85	88	87	86	85	86	85	84	83	84	83	82	82	79		

