

屋内照明器具特性	
品番 (品名)	L G D 9 4 0 4
光源	L L D 5 0 0 0 L C C 1 × 1 1 1 4 0 . 0 l m
管理番号	K 0 1 9 0 4 1 3 (0) D R 1
B Z 分類	B Z 3

器具効率	99 % 上方光束 1 % 下方光束 98 %	天井	80 %				70 %				50 %				30 %				0 %
		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
		室指数	照明率 (X 0 . 0 1) Z C M																
保守率	良 0 . 6 7	0 . 6	63	53	46	42	62	52	46	41	60	51	45	41	58	50	45	41	39
	中 0 . 6 3	0 . 8	73	64	57	53	72	63	57	52	69	62	56	52	67	60	56	52	50
	否 0 . 5 6	1 . 0	80	71	65	60	78	70	64	60	75	69	64	60	73	67	63	59	57
		1 . 2 5	85	77	72	67	83	76	71	67	81	75	70	66	78	73	69	66	63
下方投影面積 等価発光面積	cm ²	1 . 5	88	82	76	72	87	81	76	72	84	79	74	71	81	77	73	70	68
	cm ²	2 . 0	93	87	83	79	91	86	82	78	89	84	81	77	86	82	79	76	74
	取付 器具間隔最大限	2 . 5	96	91	87	84	94	90	86	83	91	88	85	82	89	86	83	81	78
	高さ 横方向 (A) 縦方向 (B)	3 . 0	98	93	90	87	96	92	89	86	93	90	87	85	91	88	86	84	81
	H m 1 . 2 6 H m 1 . 2 5 H m	4 . 0	100	97	94	91	98	95	93	90	96	93	91	89	93	91	89	87	85
		5 . 0	101	99	96	94	100	97	95	93	97	95	93	91	94	93	91	90	87
		7 . 0	103	101	99	97	101	100	98	96	99	97	96	94	96	95	94	93	90
		10 . 0	104	103	101	100	103	101	100	99	100	99	98	97	97	97	96	95	92

