

屋内照明器具特性	
品番 (品名)	L GDC1202L
光源	LED2700_70_425 ×1 425.0 l m
管理番号	K0147559 (0) DB 1
BZ分類	BZ5 / 0.7 / BZ4

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束 下方光束		1 0 0 %	室指数	照明率 (X 0 . 0 1) Z C M																					
保守率		良 中 否	0 . 6 7	0 . 6	5 8	4 6	3 9	3 3	5 7	4 6	3 8	3 3	5 5	4 5	3 8	3 3	5 2	4 4	3 8	3 3	3 1				
			0 . 6 3	0 . 8	6 8	5 7	5 0	4 4	6 7	5 6	4 9	4 4	6 4	5 5	4 9	4 4	6 2	5 4	4 8	4 3	4 1				
			0 . 5 6	1 . 0	7 5	6 5	5 7	5 2	7 3	6 4	5 7	5 1	7 1	6 2	5 6	5 1	6 8	6 1	5 5	5 1	4 9				
			1 . 2 5	8 1	7 2	6 5	5 9	7 9	7 1	6 4	5 9	7 6	6 9	6 3	5 8	7 4	6 7	6 2	5 8	5 6					
下方投影面積		c m ²	1 . 5	8 5	7 7	7 0	6 5	8 3	7 6	6 9	6 4	8 0	7 4	6 8	6 4	7 8	7 2	6 7	6 3	6 1					
等価発光面積			c m ²	2 . 0	9 0	8 3	7 8	7 3	8 9	8 2	7 7	7 3	8 6	8 0	7 6	7 2	8 3	7 8	7 5	7 1	6 9				
取付高さ	器具間隔最大限		2 . 5	9 4	8 8	8 3	7 9	9 2	8 7	8 2	7 8	8 9	8 5	8 1	7 7	8 7	8 3	7 9	7 6	7 4					
	横方向 (A) 縦方向 (B)		3 . 0	9 6	9 1	8 7	8 3	9 5	9 0	8 6	8 2	9 2	8 8	8 4	8 1	8 9	8 6	8 3	8 0	7 8					
H m	1 . 2 2 H m	1 . 2 2 H m	4 . 0	9 9	9 5	9 2	8 8	9 8	9 4	9 1	8 8	9 5	9 2	8 9	8 6	9 2	9 0	8 7	8 5	8 3					
			5 . 0	1 0 1	9 8	9 5	9 2	1 0 0	9 6	9 4	9 1	9 7	9 4	9 2	9 0	9 4	9 2	9 0	8 8	8 6					
			7 . 0	1 0 3	1 0 1	9 8	9 6	1 0 2	9 9	9 7	9 5	9 9	9 7	9 5	9 4	9 7	9 5	9 4	9 2	8 9					
			1 0 . 0	1 0 5	1 0 3	1 0 1	1 0 0	1 0 3	1 0 2	1 0 0	9 9	1 0 1	9 9	9 8	9 7	9 8	9 7	9 6	9 5	9 2					

