

屋内照明器具特性	
品番 (品名)	L G S 1 3 1 1 L
光源	LED2700_70_355 x2 355.0 lm
管理番号	K0157853 (0) DB 1
B Z 分類	BZ4 / 1.4 / BZ3

器具効率		1 0 0 % 上方光束 0 % 下方光束 1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	6 0	4 8	4 1	3 6	5 9	4 8	4 1	3 6	5 6	4 7	4 0	3 6	5 4	4 6	4 0	3 6	3 4
			0 . 6 3	0 . 8	7 0	6 0	5 3	4 7	6 9	5 9	5 2	4 7	6 6	5 8	5 2	4 7	6 4	5 7	5 1	4 7	4 5
			0 . 5 6	1 . 0	7 7	6 8	6 1	5 5	7 6	6 7	6 0	5 5	7 3	6 5	5 9	5 5	7 1	6 4	5 9	5 5	5 3
				1 . 2 5	8 3	7 5	6 8	6 3	8 2	7 4	6 8	6 3	7 9	7 2	6 7	6 2	7 6	7 1	6 6	6 2	6 0
下方投影面積		c m ²		1 . 5	8 7	7 9	7 4	6 9	8 6	7 9	7 3	6 9	8 3	7 7	7 2	6 8	8 0	7 5	7 1	6 7	6 5
			等価発光面積	c m ²	2 . 0	9 2	8 6	8 1	7 7	9 1	8 5	8 0	7 7	8 8	8 3	7 9	7 6	8 6	8 2	7 8	7 5
取付 高さ	器具間隔最大限		2 . 5	9 6	9 0	8 6	8 2	9 4	8 9	8 5	8 2	9 1	8 7	8 4	8 1	8 9	8 6	8 3	8 0	7 8	
	横方向 (A)	縦方向 (B)	3 . 0	9 8	9 3	8 9	8 6	9 6	9 2	8 9	8 6	9 4	9 0	8 7	8 4	9 1	8 8	8 6	8 3	8 1	
H m	1 . 2 0 H m	1 . 2 1 H m	4 . 0	1 0 0	9 7	9 4	9 1	9 9	9 6	9 3	9 0	9 7	9 4	9 1	8 9	9 4	9 2	9 0	8 8	8 5	
			5 . 0	1 0 2	9 9	9 7	9 4	1 0 1	9 8	9 6	9 4	9 8	9 6	9 4	9 2	9 6	9 4	9 2	9 1	8 8	
			7 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 3	1 0 1	9 9	9 7	1 0 0	9 9	9 7	9 6	9 8	9 6	9 5	9 4	9 1	
			1 0 . 0	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 3	1 0 1	1 0 0	1 0 2	1 0 0	9 9	9 8	9 9	9 8	9 7	9 7	9 4	

