

屋内照明器具特性	
品番 (品名)	L G S 1 5 0 0 N
光源	LED5000_70_445 ×1 445.0 l m
管理番号	K0157660 (0) DB 1
B Z 分類	BZ4 / 8.5 / BZ3

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %					1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		1 0 0 %	室指数	照明率 (X 0 . 0 1) Z C M																			
保守率		良 中 否	0 . 6 7	0 . 6	5 9	4 8	4 0	3 5	5 8	4 7	4 0	3 5	5 6	4 6	4 0	3 5	5 4	4 5	3 9	3 5	3 3		
			0 . 6 3	0 . 8	7 0	5 9	5 2	4 6	6 8	5 8	5 1	4 6	6 6	5 7	5 1	4 6	6 3	5 6	5 0	4 6	4 4		
			0 . 5 6	1 . 0	7 7	6 7	6 0	5 4	7 5	6 6	5 9	5 4	7 2	6 4	5 9	5 4	7 0	6 3	5 8	5 4	5 1		
				1 . 2 5	8 3	7 4	6 7	6 2	8 1	7 3	6 7	6 2	7 8	7 1	6 6	6 1	7 6	7 0	6 5	6 1	5 9		
下方投影面積		c m ²	1 . 5	8 7	7 9	7 3	6 8	8 5	7 8	7 2	6 8	8 2	7 6	7 1	6 7	8 0	7 4	7 0	6 6	6 4			
等価発光面積		c m ²	2 . 0	9 2	8 6	8 0	7 6	9 0	8 5	8 0	7 6	8 8	8 3	7 8	7 5	8 5	8 1	7 7	7 4	7 2			
取付 高さ	器具間隔最大限		2 . 5	9 5	9 0	8 5	8 1	9 4	8 9	8 5	8 1	9 1	8 7	8 3	8 0	8 8	8 5	8 2	7 9	7 7			
	横方向 (A)	縦方向 (B)	3 . 0	9 7	9 3	8 9	8 5	9 6	9 2	8 8	8 5	9 3	9 0	8 6	8 4	9 1	8 8	8 5	8 3	8 0			
H m	1 . 2 4 H m	1 . 2 3 H m	4 . 0	1 0 0	9 7	9 3	9 0	9 9	9 5	9 2	9 0	9 6	9 3	9 1	8 8	9 4	9 1	8 9	8 7	8 5			
			5 . 0	1 0 2	9 9	9 6	9 4	1 0 0	9 8	9 5	9 3	9 8	9 6	9 3	9 1	9 5	9 3	9 2	9 0	8 7			
			7 . 0	1 0 4	1 0 1	9 9	9 8	1 0 2	1 0 0	9 8	9 7	1 0 0	9 8	9 7	9 5	9 7	9 6	9 5	9 3	9 1			
			1 0 . 0	1 0 5	1 0 3	1 0 2	1 0 1	1 0 4	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 3			

