

屋内照明器具特性	
品番 (品名)	L G S 3 0 2 3
光源	L E D 2 7 0 0 _ 7 0 _ 6 8 0 × 1 6 8 0 . 0 l m
管理番号	K 0 1 6 4 3 9 2 (0) D B 1
B Z 分類	B Z 1

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																				Z C M
下方光束		1 0 0 %																						
保守率		良 中 否	0 . 6	8 1	7 4	6 9	6 6	8 0	7 3	6 9	6 6	7 8	7 3	6 9	6 6	7 7	7 2	6 8	6 6	6 5				
			0 . 6 3	0 . 8	8 7	8 1	7 7	7 4	8 6	8 0	7 6	7 3	8 5	8 0	7 6	7 3	8 3	7 9	7 5	7 3	7 2			
			1 . 0	9 1	8 6	8 2	7 9	9 0	8 5	8 1	7 8	8 8	8 4	8 1	7 8	8 7	8 3	8 0	7 8	7 6				
			0 . 5 6	1 . 2 5	9 5	9 0	8 6	8 3	9 4	8 9	8 6	8 3	9 2	8 8	8 5	8 2	9 0	8 7	8 4	8 2	8 0			
下方投影面積		c m ²	1 . 5	9 7	9 3	8 9	8 7	9 6	9 2	8 9	8 6	9 4	9 1	8 8	8 6	9 2	8 9	8 7	8 5	8 3				
			2 . 0	1 0 0	9 6	9 4	9 1	9 9	9 6	9 3	9 1	9 7	9 4	9 2	9 0	9 5	9 3	9 1	8 9	8 7				
取付 高さ	器具間隔最大限		2 . 5	1 0 2	9 9	9 6	9 4	1 0 1	9 8	9 6	9 4	9 9	9 6	9 4	9 3	9 7	9 5	9 3	9 2	9 0				
	横方向 (A)	縦方向 (B)	3 . 0	1 0 3	1 0 0	9 8	9 6	1 0 2	9 9	9 7	9 6	1 0 0	9 8	9 6	9 4	9 8	9 6	9 5	9 3	9 1				
H m	0 . 4 7 H m	0 . 4 7 H m	4 . 0	1 0 4	1 0 2	1 0 1	9 9	1 0 3	1 0 1	1 0 0	9 8	1 0 1	1 0 0	9 8	9 7	9 9	9 8	9 7	9 6	9 3				
			5 . 0	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 3	1 0 1	1 0 0	1 0 2	1 0 1	1 0 0	9 8	1 0 0	9 9	9 8	9 7	9 5				
			7 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 9	9 6				
			1 0 . 0	1 0 7	1 0 6	1 0 5	1 0 5	1 0 6	1 0 5	1 0 4	1 0 4	1 0 4	1 0 3	1 0 2	1 0 2	1 0 1	1 0 1	1 0 0	1 0 0	9 7				

