

屋内照明器具特性	
品番 (品名)	LGS3520L
光源	LED2700_70_680 ×1 680.0 l m
管理番号	K0161680 (0) DR 1
BZ分類	BZ1 / 1.1 / BZ2 / 8.5 / BZ1

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																				Z C M
下方光束		1 0 0 %																						
保守率		良	0 . 6 7	0 . 6	7 3	6 4	5 9	5 5	7 2	6 4	5 8	5 5	7 0	6 3	5 8	5 5	6 8	6 2	5 8	5 5	5 3			
		中	0 . 6 3	0 . 8	8 0	7 2	6 7	6 3	7 9	7 2	6 7	6 3	7 7	7 1	6 6	6 3	7 5	7 0	6 6	6 3	6 1			
		否	0 . 5 6	1 . 0	8 5	7 8	7 3	6 9	8 4	7 7	7 3	6 9	8 2	7 6	7 2	6 9	8 0	7 5	7 1	6 8	6 7			
				1 . 2 5	9 0	8 3	7 8	7 5	8 8	8 2	7 8	7 5	8 6	8 1	7 7	7 4	8 4	8 0	7 6	7 4	7 2			
下方投影面積		c m ²	1 . 5	9 3	8 7	8 3	7 9	9 1	8 6	8 2	7 9	8 9	8 5	8 1	7 8	8 7	8 3	8 0	7 7	7 6				
等価発光面積			c m ²	2 . 0	9 6	9 2	8 8	8 5	9 5	9 1	8 7	8 4	9 3	8 9	8 6	8 4	9 1	8 8	8 5	8 3	8 1			
取付	器具間隔最大限			2 . 5	9 9	9 5	9 2	8 9	9 7	9 4	9 1	8 8	9 5	9 2	9 0	8 7	9 3	9 0	8 8	8 6	8 4			
高さ	横方向 (A)		縦方向 (B)	3 . 0	1 0 0	9 7	9 4	9 2	9 9	9 6	9 3	9 1	9 7	9 4	9 2	9 0	9 4	9 2	9 0	8 9	8 7			
H m	0 . 4 5 H m		0 . 4 5 H m	4 . 0	1 0 2	1 0 0	9 7	9 5	1 0 1	9 9	9 6	9 5	9 9	9 7	9 5	9 3	9 6	9 5	9 3	9 2	9 0			
				5 . 0	1 0 3	1 0 1	9 9	9 8	1 0 2	1 0 0	9 8	9 7	1 0 0	9 8	9 7	9 5	9 8	9 6	9 5	9 4	9 1			
				7 . 0	1 0 5	1 0 3	1 0 2	1 0 0	1 0 3	1 0 2	1 0 1	9 9	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 4			
				1 0 . 0	1 0 6	1 0 5	1 0 3	1 0 2	1 0 4	1 0 3	1 0 2	1 0 2	1 0 2	1 0 1	1 0 0	1 0 0	1 0 0	9 9	9 9	9 8	9 5			

