

屋内照明器具特性	
品番 (品名)	L G S 9 0 0 0
光源	L L D 3 0 2 0 L C B 1 × 1 7 9 5 . 0 l m
管理番号	K 0 1 7 9 4 6 4 (0) D R 1
B Z 分類	B Z 1

器具効率		88 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %				10 %				10 %				10 %			
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																	Z C M
下方光束		88 %																			
保守率		良	0 . 6	72	66	63	60	71	66	63	60	70	66	62	60	69	65	62	60	59	
		中	0 . 8	77	72	69	66	77	72	68	66	75	71	68	66	74	70	68	66	64	
		否	0 . 63	1 . 0	81	76	73	70	80	76	72	70	78	75	72	70	77	74	71	69	68
			0 . 56	1 . 25	84	79	76	74	83	79	76	74	81	78	75	73	79	77	74	73	71
下方投影面積		c m ²	1 . 5	85	82	79	76	84	81	78	76	83	80	77	76	81	79	77	75	74	
等価発光面積			c m ²	2 . 0	88	85	82	80	87	84	82	80	85	83	81	79	83	81	80	78	77
取付高さ	器具間隔最大限		2 . 5	89	87	84	83	88	86	84	82	86	84	83	81	85	83	82	80	79	
	横方向 (A)		縦方向 (B)	3 . 0	90	88	86	84	89	87	85	84	87	86	84	83	86	84	83	82	80
H m	0 . 40 H m	0 . 40 H m	4 . 0	92	90	88	87	91	89	87	86	89	87	86	85	87	86	85	84	82	
			5 . 0	92	91	89	88	91	90	89	88	89	88	87	86	88	87	86	85	83	
			7 . 0	93	92	91	90	92	91	90	89	90	89	89	88	88	88	87	86	84	
			10 . 0	94	93	92	92	93	92	91	91	91	90	90	89	89	88	88	88	85	

