

屋内照明器具特性	
品番 (品名)	L G S 9 0 0 0
光源	L L D 3 0 2 0 M L C B 1 × 1 7 1 5 . 0 l m
管理番号	K 0 1 7 9 4 6 6 (0) D R 1
B Z 分類	B Z 1

器具効率		9 4 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																		Z C M	
下方光束		9 4 %																					
保守率		良 中 否	0 . 6	7 7	7 1	6 7	6 4	7 6	7 0	6 7	6 4	7 5	7 0	6 6	6 4	7 4	6 9	6 6	6 4	6 3			
			0 . 8	8 2	7 7	7 3	7 0	8 2	7 6	7 3	7 0	8 0	7 6	7 2	7 0	7 9	7 5	7 2	7 0	6 9			
			1 . 0	8 6	8 1	7 7	7 5	8 5	8 0	7 7	7 4	8 3	7 9	7 6	7 4	8 2	7 8	7 6	7 4	7 3			
			0 . 5 6	1 . 2 5	8 9	8 4	8 1	7 9	8 8	8 4	8 1	7 8	8 6	8 3	8 0	7 8	8 5	8 2	7 9	7 7	7 6		
下方投影面積		c m ²	1 . 5	9 1	8 7	8 4	8 1	9 0	8 6	8 3	8 1	8 8	8 5	8 3	8 0	8 6	8 4	8 2	8 0	7 8			
			等価発光面積		c m ²	2 . 0	9 3	9 0	8 8	8 5	9 2	8 9	8 7	8 5	9 1	8 8	8 6	8 4	8 9	8 7	8 5	8 3	8 2
取付 高さ	器具間隔最大限					2 . 5	9 5	9 2	9 0	8 8	9 4	9 1	8 9	8 7	9 2	9 0	8 8	8 6	9 0	8 8	8 7	8 6	8 4
		横方向 (A)	縦方向 (B)	3 . 0	9 6	9 4	9 2	9 0	9 5	9 3	9 1	8 9	9 3	9 1	9 0	8 8	9 1	9 0	8 8	8 7	8 5		
H m	0 . 4 0 H m	0 . 4 0 H m	4 . 0	9 7	9 6	9 4	9 2	9 6	9 5	9 3	9 2	9 4	9 3	9 2	9 0	9 2	9 1	9 0	8 9	8 7			
			5 . 0	9 8	9 7	9 5	9 4	9 7	9 6	9 4	9 3	9 5	9 4	9 3	9 2	9 3	9 2	9 1	9 0	8 8			
			7 . 0	9 9	9 8	9 7	9 6	9 8	9 7	9 6	9 5	9 6	9 5	9 4	9 4	9 4	9 3	9 3	9 2	9 0			
			1 0 . 0	1 0 0	9 9	9 8	9 7	9 9	9 8	9 7	9 7	9 7	9 6	9 5	9 5	9 5	9 4	9 4	9 3	9 1			

