

屋内照明器具特性	
品番 (品名)	L G S 9 0 0 0
光源	LLD40402CQ1 (KAKUSAN) ×1 860.0 l m
管理番号	K0184312 (0) DR 1
B Z 分類	BZ5 / 0.7 / BZ4

器具効率		80 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
				室指数	照明率 (X0.01)																	
保守率		良 中 否	0.67	0.6	47	37	31	27	46	37	31	27	44	36	30	26	42	35	30	26	25	
			0.63	0.8	55	46	40	35	54	45	39	35	51	44	39	35	50	43	38	35	33	
			0.56	1.0	60	52	46	41	59	51	46	41	57	50	45	41	55	49	44	41	39	
				1.25	65	57	52	48	64	57	51	47	61	55	51	47	59	54	50	47	45	
下方投影面積		c m ²		1.5	68	61	56	52	67	61	56	52	64	59	55	51	62	58	54	51	49	
等価発光面積			c m ²	2.0	73	67	62	59	71	66	62	58	69	65	61	58	67	63	60	57	55	
取付 高さ	器具間隔最大限			2.5	75	71	67	63	74	70	66	63	72	68	65	62	70	66	64	61	59	
	横方向 (A)			縦方向 (B)		3.0	77	73	69	66	76	72	69	66	74	70	68	65	71	69	66	64
H m	1.27 H m	1.27 H m		4.0	80	76	73	71	78	75	73	70	76	74	71	69	74	72	70	68	66	
			5.0	81	78	76	74	80	77	75	73	78	76	74	72	76	74	72	71	69		
			7.0	83	81	79	77	82	80	78	76	79	78	76	75	77	76	75	74	72		
			10.0	84	82	81	80	83	82	80	79	81	80	79	78	79	78	77	76	74		

