

屋内照明器具特性	
品番 (品名)	L G S 9 0 0 1
光源	L L D 5 0 0 0 L C C 1 × 1 1 1 4 0 . 0 l m
管理番号	K 0 1 9 0 4 5 0 (0) D R 1
B Z 分類	B Z 3

器具効率		1 0 0 %		反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
					壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
					照明率 (X 0 . 0 1) Z C M																	
保守率		良 中 否	0 . 6 7	0 . 6	6 4	5 3	4 6	4 2	6 2	5 3	4 6	4 2	6 0	5 1	4 6	4 1	5 8	5 0	4 5	4 1	3 9	
			0 . 6 3	0 . 8	7 4	6 4	5 8	5 3	7 2	6 3	5 7	5 3	7 0	6 2	5 6	5 2	6 7	6 1	5 6	5 2	5 0	
			0 . 5 6	1 . 0	8 0	7 1	6 5	6 1	7 9	7 1	6 5	6 0	7 6	6 9	6 4	6 0	7 3	6 7	6 3	5 9	5 7	
			1 . 2 5	8 5	7 8	7 2	6 8	8 4	7 7	7 1	6 7	8 1	7 5	7 0	6 6	7 8	7 3	6 9	6 6	6 3		
下方投影面積		c m ²	1 . 5	8 9	8 2	7 7	7 2	8 7	8 1	7 6	7 2	8 4	7 9	7 5	7 1	8 1	7 7	7 3	7 0	6 8		
			等価発光面積		c m ²	2 . 0	9 3	8 8	8 3	7 9	9 2	8 7	8 2	7 9	8 9	8 4	8 1	7 8	8 6	8 2	7 9	7 6
取付高さ	器具間隔最大限					2 . 5	9 6	9 1	8 7	8 4	9 5	9 0	8 6	8 3	9 2	8 8	8 5	8 2	8 9	8 6	8 3	8 1
		横方向 (A)	縦方向 (B)	3 . 0	9 8	9 4	9 0	8 7	9 7	9 3	8 9	8 6	9 3	9 0	8 7	8 5	9 1	8 8	8 6	8 3	8 1	
H m	1 . 2 5 H m	1 . 2 5 H m	4 . 0	1 0 0	9 7	9 4	9 2	9 9	9 6	9 3	9 1	9 6	9 3	9 1	8 9	9 3	9 1	8 9	8 7	8 4		
			5 . 0	1 0 2	9 9	9 7	9 4	1 0 0	9 8	9 6	9 4	9 7	9 5	9 3	9 2	9 4	9 3	9 1	9 0	8 6		
			7 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 2	1 0 0	9 8	9 7	9 9	9 7	9 6	9 5	9 6	9 5	9 4	9 3	8 9		
			1 0 . 0	1 0 5	1 0 3	1 0 2	1 0 1	1 0 3	1 0 2	1 0 1	9 9	1 0 0	9 9	9 8	9 7	9 7	9 7	9 6	9 5	9 1		

