

屋内照明器具特性	
品番 (品名)	LGS9500
光源	LLD2020LCB1 ×1 460.0 l m
管理番号	K0179467 (0) DR 1
B Z 分類	BZ1

器具効率		96 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束		0 %	室指数	照明率 (X0.01)																		Z C M
下方光束		96 %																				
保守率		良 中 否	0.67	0.6	78	72	68	65	78	72	68	65	76	71	68	65	75	71	67	65	64	
			0.63	0.8	84	79	75	72	83	78	74	72	82	77	74	72	80	76	74	71	70	
			0.56	1.0	88	83	79	76	87	82	79	76	85	81	78	76	84	80	77	75	74	
				1.25	91	86	83	80	90	86	82	80	88	84	82	79	86	83	81	79	78	
下方投影面積		c m ²		1.5	93	89	86	83	92	88	85	83	90	87	84	82	88	86	83	82	80	
等価発光面積			c m ²	2.0	95	92	89	87	94	91	89	87	92	90	88	86	91	88	87	85	83	
取付 高さ	器具間隔最大限		2.5	97	94	92	90	96	93	91	89	94	92	90	88	92	90	89	87	85		
	横方向 (A)		縦方向 (B)	3.0	98	96	94	92	97	95	93	91	95	93	91	90	93	92	90	89	87	
H m	0.40 H m	0.40 H m	4.0	99	98	96	94	98	97	95	94	96	95	94	92	94	93	92	91	89		
			5.0	100	99	97	96	99	98	96	95	97	96	95	94	95	94	93	92	90		
			7.0	100	100	99	98	100	99	98	97	98	97	96	95	96	95	95	94	91		
			10.0	102	101	100	100	101	100	99	99	99	98	97	97	97	96	96	95	93		

