

屋内照明器具特性	
品番 (品名)	LGS9500
光源	LLD40402CQ1 (SHUKOU) ×1 620.0 l m
管理番号	K0184321 (0) DR 1
BZ分類	BZ1

器具効率		9 4 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		9 4 %																				
保守率		良 中 否	0 . 6	7 1	6 4	5 9	5 6	7 0	6 4	5 9	5 6	6 9	6 3	5 9	5 6	6 8	6 2	5 9	5 6	5 5		
			0 . 6 3	0 . 8	7 8	7 2	6 7	6 4	7 7	7 1	6 7	6 4	7 6	7 0	6 7	6 4	7 4	7 0	6 6	6 4	6 2	
			1 . 0	8 3	7 7	7 3	6 9	8 2	7 6	7 2	6 9	8 0	7 5	7 2	6 9	7 8	7 4	7 1	6 9	6 7		
			0 . 5 6	1 . 2 5	8 6	8 1	7 7	7 4	8 5	8 0	7 7	7 4	8 3	7 9	7 6	7 3	8 2	7 8	7 5	7 3	7 1	
下方投影面積		c m ²	1 . 5	8 9	8 4	8 0	7 8	8 8	8 3	8 0	7 7	8 6	8 2	7 9	7 7	8 4	8 1	7 8	7 6	7 5		
			等価発光面積		c m ²	2 . 0	9 2	8 8	8 5	8 2	9 1	8 7	8 4	8 2	8 9	8 6	8 3	8 1	8 7	8 4	8 2	8 0
取付 高さ	器具間隔最大限					2 . 5	9 4	9 1	8 8	8 6	9 3	9 0	8 7	8 5	9 1	8 8	8 6	8 4	8 9	8 7	8 5	8 3
	横方向 (A)		縦方向 (B)		3 . 0	9 5	9 2	9 0	8 8	9 4	9 1	8 9	8 7	9 2	9 0	8 8	8 6	9 0	8 8	8 6	8 5	8 3
H m	0 . 7 2 H m	0 . 7 2 H m	4 . 0	9 7	9 4	9 2	9 1	9 5	9 3	9 2	9 0	9 3	9 2	9 0	8 9	9 1	9 0	8 9	8 8	8 5		
			5 . 0	9 8	9 6	9 4	9 3	9 6	9 5	9 3	9 2	9 4	9 3	9 2	9 1	9 2	9 1	9 0	8 9	8 7		
			7 . 0	9 9	9 7	9 6	9 5	9 8	9 6	9 5	9 4	9 5	9 4	9 3	9 3	9 3	9 3	9 2	9 1	8 9		
			1 0 . 0	9 9	9 8	9 8	9 7	9 8	9 7	9 7	9 6	9 6	9 5	9 5	9 4	9 4	9 4	9 3	9 2	9 0		

