

| 屋内照明器具特性 |                           |
|----------|---------------------------|
| 品番 (品名)  | LGS9500                   |
| 光源       | LLD5010LCC1 ×1 1095.0 l m |
| 管理番号     | K0190448 ( 0 ) DR 1       |
| B Z 分類   | BZ1                       |

| 器具効率     |           | 100 %            | 反射率              | 天井            | 80 % |     |     |     | 70 % |     |     |     | 50 % |     |     |    | 30 % |    |    |    | 0 % |       |
|----------|-----------|------------------|------------------|---------------|------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|----|------|----|----|----|-----|-------|
|          |           |                  |                  | 壁             | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10 | 70   | 50 | 30 | 10 | 0 % |       |
|          |           |                  |                  | 床             | 10 % |     |     |     | 10 % |     |     |     | 10 % |     |     |    | 10 % |    |    |    | 0 % |       |
| 上方光束     |           | 98 %             | 室指数              | 照明率 ( X0.01 ) |      |     |     |     |      |     |     |     |      |     |     |    |      |    |    |    |     | Z C M |
| 下方光束     |           |                  |                  |               |      |     |     |     |      |     |     |     |      |     |     |    |      |    |    |    |     |       |
| 保守率      |           | 良<br>中<br>否      | 0.67             | 0.6           | 83   | 77  | 73  | 71  | 82   | 77  | 73  | 70  | 81   | 76  | 72  | 70 | 79   | 75 | 72 | 70 | 69  |       |
|          |           |                  | 0.63             | 0.8           | 89   | 83  | 79  | 76  | 88   | 82  | 79  | 76  | 86   | 81  | 78  | 76 | 84   | 80 | 77 | 75 | 74  |       |
|          |           |                  | 0.56             | 1.0           | 92   | 87  | 83  | 80  | 91   | 86  | 83  | 80  | 89   | 85  | 82  | 80 | 87   | 84 | 81 | 79 | 77  |       |
|          |           |                  |                  | 1.25          | 95   | 90  | 87  | 84  | 94   | 89  | 86  | 84  | 92   | 88  | 85  | 83 | 90   | 87 | 84 | 82 | 81  |       |
| 下方投影面積   |           | c m <sup>2</sup> | 1.5              | 97            | 93   | 89  | 87  | 96  | 92   | 89  | 86  | 93  | 90   | 88  | 85  | 91 | 89   | 86 | 85 | 83 |     |       |
| 等価発光面積   |           |                  | c m <sup>2</sup> | 2.0           | 99   | 96  | 93  | 91  | 98   | 95  | 92  | 90  | 96   | 93  | 91  | 89 | 93   | 91 | 89 | 88 | 86  |       |
| 取付<br>高さ | 器具間隔最大限   |                  | 2.5              | 101           | 98   | 95  | 93  | 100 | 97   | 95  | 93  | 97  | 95   | 93  | 91  | 95 | 93   | 91 | 90 | 88 |     |       |
|          | 横方向 ( A ) | 縦方向 ( B )        | 3.0              | 102           | 99   | 97  | 95  | 101 | 98   | 96  | 95  | 98  | 96   | 95  | 93  | 96 | 94   | 93 | 92 | 89 |     |       |
| H m      | 0.81 H m  | 0.80 H m         | 4.0              | 103           | 101  | 100 | 98  | 102 | 100  | 99  | 97  | 99  | 98   | 97  | 95  | 97 | 96   | 95 | 94 | 91 |     |       |
|          |           |                  | 5.0              | 104           | 103  | 101 | 100 | 103 | 101  | 100 | 99  | 100 | 99   | 98  | 97  | 98 | 97   | 96 | 95 | 92 |     |       |
|          |           |                  | 7.0              | 105           | 104  | 103 | 102 | 104 | 103  | 102 | 101 | 101 | 100  | 99  | 99  | 99 | 98   | 97 | 96 | 93 |     |       |
|          |           |                  | 10.0             | 106           | 105  | 104 | 103 | 105 | 104  | 103 | 102 | 102 | 101  | 101 | 100 | 99 | 99   | 98 | 98 | 94 |     |       |

