

屋内照明器具特性	
品番 (品名)	L G S 9 5 0 1
光源	LLD2000LCB1 ×1 531.0 lm
管理番号	K0179457 (0) DR 1
B Z 分類	BZ5/2.8/BZ4/3.5/BZ5/4.5/BZ4 / 6.0/BZ5/8.5/BZ4

器具効率		75 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	室指数	照明率 (X0.01)																			Z	CM
下方光束		75 %																						
保守率		良 中 否	0.67	0.6	43	34	28	24	42	33	28	24	40	33	27	24	39	32	27	24	22			
			0.63	0.8	51	42	36	32	49	41	36	32	47	40	35	32	46	39	35	31	30			
			0.56	1.0	56	48	42	38	54	47	42	37	52	46	41	37	50	45	40	37	35			
				1.25	60	53	48	43	59	52	47	43	57	51	46	43	55	50	46	42	41			
下方投影面積		cm ²	1.5	63	57	52	48	62	56	51	47	60	55	50	47	58	53	50	46	45				
			等価発光面積		cm ²	2.0	67	62	58	54	66	61	57	54	64	60	56	53	62	58	55	52	51	
						2.5	70	65	62	58	69	65	61	58	67	63	60	57	65	62	59	56	55	
取付 高さ	器具間隔最大限		3.0	72	68	64	61	71	67	64	61	69	65	63	60	67	64	62	59	57				
	横方向 (A)	縦方向 (B)		4.0	74	71	68	66	73	70	68	65	71	69	66	64	69	67	65	63	61			
H m	1.26 H m	1.26 H m	5.0	76	73	71	69	75	72	70	68	73	71	69	67	71	69	67	66	64				
			7.0	77	75	74	72	76	75	73	71	74	73	71	70	72	71	70	69	67				
			10.0	79	77	76	75	78	76	75	74	76	75	74	73	74	73	72	71	69				

