

屋内照明器具特性

品番 (品名)	L G W 7 1 8 0 7	
光源	LED2700_70_640 x1	640.0 l m
管理番号	K0140469 (0) DB 1	
B Z 分類	B Z 5	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	4 %																			
下方光束	96 %																			
室指数	照明率 (X 0 . 0 1)																		Z C M	
保守率	良 0.69 中 0.67 否 0.63	0.6	55	43	35	30	54	42	35	29	51	41	34	29	48	39	33	29	26	
		0.8	65	54	46	40	64	53	45	40	60	51	44	39	57	49	43	38	36	
		1.0	72	61	53	47	70	60	52	47	66	58	51	46	63	56	50	45	43	
		1.25	78	68	60	55	76	67	60	54	72	64	58	53	69	62	57	52	49	
下方投影面積	c m ²	1.5	82	73	66	60	80	72	65	60	76	69	63	59	73	67	62	58	54	
		2.0	88	80	74	69	86	79	73	68	82	76	71	67	78	73	69	65	62	
取付高さ	器具間隔最大限		2.5	91	85	79	74	89	83	78	74	85	80	76	72	82	78	74	70	67
	横方向 (A)	縦方向 (B)	3.0	94	88	83	79	92	86	82	78	88	83	80	76	84	81	77	74	71
H m	1.29 H m	1.29 H m	4.0	97	92	88	85	95	91	87	84	91	88	84	82	88	85	82	80	76
			5.0	99	95	92	88	97	93	90	87	93	90	88	85	90	87	85	83	79
			7.0	101	98	96	93	99	97	94	92	96	94	91	89	92	91	89	87	83
			10.0	103	101	99	97	101	99	97	96	98	96	94	93	94	93	92	90	86

