

屋内照明器具特性	
品番 (品名)	LRD1030L
光源	LED2700_70_210 ×1 210.0 l m
管理番号	K0161901 (1) DB 1
B Z 分類	BZ1

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
上方光束		0 %	室指数	床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
下方光束		1 0 0 %		照明率 (X 0 . 0 1) Z C M																	
保守率		良 中 否	0 . 6 7	0 . 6	9 6	9 3	9 1	8 9	9 6	9 3	9 1	8 9	9 5	9 2	9 0	8 9	9 4	9 2	9 0	8 9	8 8
			0 . 6 3	0 . 8	9 9	9 6	9 4	9 2	9 8	9 6	9 4	9 2	9 7	9 5	9 3	9 2	9 6	9 4	9 3	9 2	9 1
			0 . 5 6	1 . 0	1 0 1	9 8	9 6	9 5	1 0 0	9 8	9 6	9 4	9 9	9 7	9 5	9 4	9 8	9 6	9 5	9 4	9 3
				1 . 2 5	1 0 2	1 0 0	9 8	9 7	1 0 1	9 9	9 8	9 6	1 0 0	9 8	9 7	9 6	9 9	9 7	9 6	9 5	9 4
下方投影面積		c m ²	等価発光面積 c m ²	1 . 5	1 0 3	1 0 1	9 9	9 8	1 0 2	1 0 0	9 9	9 8	1 0 1	9 9	9 8	9 7	1 0 0	9 8	9 7	9 6	9 5
等価発光面積		c m ²		2 . 0	1 0 4	1 0 3	1 0 1	1 0 0	1 0 3	1 0 2	1 0 1	9 9	1 0 2	1 0 1	9 9	9 8	1 0 0	9 9	9 8	9 8	9 6
取付 高さ	器具間隔最大限			2 . 5	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	1 0 0	1 0 1	1 0 0	9 9	9 8	9 7
	横方向 (A) 縦方向 (B)			3 . 0	1 0 6	1 0 4	1 0 3	1 0 2	1 0 5	1 0 3	1 0 2	1 0 1	1 0 3	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	1 0 0	9 9	9 7
H m	0 . 3 7 H m 0 . 3 7 H m		4 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 3	1 0 3	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	1 0 0	9 8	
			5 . 0	1 0 7	1 0 6	1 0 5	1 0 4	1 0 6	1 0 5	1 0 4	1 0 3	1 0 4	1 0 3	1 0 2	1 0 2	1 0 2	1 0 1	1 0 1	1 0 0	9 8	
			7 . 0	1 0 7	1 0 6	1 0 6	1 0 5	1 0 6	1 0 5	1 0 5	1 0 4	1 0 4	1 0 4	1 0 3	1 0 3	1 0 2	1 0 2	1 0 1	1 0 1	9 9	
			1 0 . 0	1 0 7	1 0 7	1 0 7	1 0 6	1 0 6	1 0 6	1 0 5	1 0 4	1 0 4	1 0 4	1 0 3	1 0 2	1 0 2	1 0 2	1 0 2	1 0 2	9 9	

