

屋内照明器具特性	
品番 (品名)	L R D 3 1 0 1 L
光源	LED2700_70_550 ×1 550.0 lm
管理番号	K0160147 (2) DB 1
B Z 分類	BZ3 / 2.3 / BZ2 / 4.5 / BZ3 / 6.0 / BZ2

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01) ZCM															
保守率		良 中 否	0.67	0.6	63	52	46	41	62	52	45	41	60	51	45	41	58	50	44	40	39	
			0.63	0.8	74	64	58	53	73	64	57	53	70	62	57	52	68	61	56	52	50	
			0.56	1.0	81	72	66	61	79	71	65	61	77	70	65	61	75	69	64	60	58	
				1.25	86	79	73	69	85	78	73	68	82	76	72	68	80	75	71	68	66	
下方投影面積		cm ²	1.5	90	83	78	74	89	82	78	74	86	81	77	73	84	79	76	72	70		
			2.0	95	89	85	81	93	88	84	81	91	87	83	80	88	85	82	79	77		
等価発光面積		cm ²	2.5	98	93	89	86	96	92	89	86	94	90	87	85	91	88	86	84	81		
			3.0	99	96	92	89	98	95	91	89	96	93	90	88	93	91	89	87	84		
Hm	1.18Hm		1.18Hm		4.0	102	99	96	94	100	98	95	93	98	96	94	92	96	94	90	88	
					5.0	103	101	98	96	102	100	97	96	99	97	96	94	97	96	94	90	
					7.0	105	103	101	100	103	102	100	99	101	100	98	97	99	98	96	93	
					10.0	106	104	103	102	104	103	102	101	102	101	100	99	100	99	98	95	

