

屋内照明器具特性	
品番 (品名)	L R D 3 1 0 2 V
光源	LED3500_70_650 ×1 650.0 lm
管理番号	K0160145 (0) DB 1
B Z 分類	B Z 3

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																		Z C M	
下方光束				1 0 0 %																			
保守率		良 中 否	0 . 6 7	0 . 6	6 3	5 2	4 5	4 0	6 1	5 1	4 5	4 0	5 9	5 0	4 4	4 0	5 7	4 9	4 4	4 0	3 8		
			0 . 6 3	0 . 8	7 3	6 3	5 7	5 2	7 2	6 3	5 6	5 2	6 9	6 1	5 6	5 1	6 7	6 0	5 5	5 1	4 9		
			0 . 5 6	1 . 0	8 0	7 1	6 5	6 0	7 9	7 0	6 4	6 0	7 6	6 9	6 4	5 9	7 4	6 8	6 3	5 9	5 7		
				1 . 2 5	8 6	7 8	7 2	6 8	8 4	7 7	7 2	6 7	8 2	7 6	7 1	6 7	7 9	7 4	7 0	6 6	6 4		
下方投影面積		c m ²	1 . 5	8 9	8 2	7 7	7 3	8 8	8 2	7 7	7 3	8 5	8 0	7 6	7 2	8 3	7 8	7 5	7 1	6 9			
等価発光面積			c m ²	2 . 0	9 4	8 9	8 4	8 0	9 3	8 8	8 3	8 0	9 0	8 6	8 2	7 9	8 8	8 4	8 1	7 8	7 6		
取付高さ	器具間隔最大限			2 . 5	9 7	9 2	8 9	8 5	9 6	9 1	8 8	8 5	9 3	9 0	8 6	8 4	9 1	8 8	8 5	8 3	8 0		
		横方向 (A)		縦方向 (B)		3 . 0	9 9	9 5	9 2	8 9	9 8	9 4	9 1	8 8	9 5	9 2	8 9	8 7	9 3	9 0	8 8	8 6	8 3
H m	1 . 1 9 H m	1 . 1 9 H m	4 . 0	1 0 1	9 8	9 5	9 3	1 0 0	9 7	9 5	9 2	9 8	9 5	9 3	9 1	9 5	9 3	9 1	9 0	8 7			
			5 . 0	1 0 3	1 0 0	9 8	9 6	1 0 1	9 9	9 7	9 5	9 9	9 7	9 5	9 4	9 7	9 5	9 4	9 2	9 0			
			7 . 0	1 0 4	1 0 2	1 0 1	9 9	1 0 3	1 0 1	1 0 0	9 8	1 0 1	9 9	9 8	9 7	9 8	9 7	9 6	9 5	9 2			
			1 0 . 0	1 0 6	1 0 4	1 0 3	1 0 2	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 7	9 4			

