

屋内照明器具特性	
品番 (品名)	L R D 3 2 0 0 L
光源	LED2700_70_750 ×1 750.0 l m
管理番号	K0148419 (0) DB 1
B Z 分類	BZ4 / 3.5 / BZ3

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1)																Z C M
保守率		良 中 否	0 . 6 9	0 . 6	5 9	4 7	4 0	3 5	5 8	4 7	4 0	3 5	5 5	4 6	3 9	3 4	5 3	4 5	3 9	3 4	3 2
			0 . 6 7	0 . 8	6 9	5 9	5 1	4 6	6 8	5 8	5 1	4 6	6 5	5 7	5 0	4 5	6 3	5 5	5 0	4 5	4 3
			0 . 6 3	1 . 0	7 6	6 6	5 9	5 4	7 5	6 5	5 9	5 4	7 2	6 4	5 8	5 3	6 9	6 2	5 7	5 3	5 1
				1 . 2 5	8 2	7 3	6 7	6 2	8 1	7 3	6 6	6 1	7 8	7 1	6 5	6 1	7 5	6 9	6 4	6 1	5 8
下方投影面積		c m ²	1 . 5	8 6	7 8	7 2	6 7	8 5	7 8	7 2	6 7	8 2	7 6	7 1	6 7	7 9	7 4	7 0	6 6	6 4	
			等価発光面積		c m ²	2 . 0	9 2	8 5	8 0	7 6	9 0	8 4	8 0	7 5	8 8	8 3	7 8	7 5	8 5	8 1	7 7
取付高さ	器具間隔最大限					2 . 5	9 5	9 0	8 5	8 1	9 4	8 9	8 5	8 1	9 1	8 7	8 3	8 0	8 8	8 5	8 2
		横方向 (A)	縦方向 (B)	3 . 0	9 7	9 3	8 9	8 5	9 6	9 2	8 8	8 5	9 3	9 0	8 7	8 4	9 1	8 8	8 5	8 3	8 0
H m	1 . 2 1 H m	1 . 2 1 H m	4 . 0	1 0 0	9 7	9 3	9 1	9 9	9 5	9 3	9 0	9 6	9 3	9 1	8 9	9 4	9 1	8 9	8 7	8 5	
			5 . 0	1 0 2	9 9	9 6	9 4	1 0 0	9 8	9 5	9 3	9 8	9 6	9 4	9 2	9 5	9 4	9 2	9 0	8 8	
			7 . 0	1 0 4	1 0 1	1 0 0	9 8	1 0 2	1 0 0	9 9	9 7	1 0 0	9 8	9 7	9 5	9 7	9 6	9 5	9 4	9 1	
			1 0 . 0	1 0 5	1 0 3	1 0 2	1 0 1	1 0 4	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 3	

