

屋内照明器具特性	
品番 (品名)	L R D 9 1 0 0
光源	L L D 4 0 4 0 2 C Q 1 (K A K U S A N) × 1 8 6 0 . 0 1 m
管理番号	K 0 1 8 4 5 1 5 (0) D R 1
B Z 分類	B Z 3

器具効率		55 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 63	0 . 6	34	29	25	22	34	28	25	22	33	28	24	22	32	27	24	22	21
			0 . 6	0 . 8	40	34	31	28	39	34	30	28	38	33	30	28	37	33	30	28	27
			0 . 56	1 . 0	43	38	35	32	42	38	35	32	41	37	34	32	40	36	34	32	31
				1 . 25	46	42	39	36	45	41	38	36	44	40	38	36	43	40	37	35	34
下方投影面積 等価発光面積		cm ² cm ²		1 . 5	48	44	41	39	47	44	41	39	46	43	40	38	45	42	40	38	37
				2 . 0	51	48	45	43	50	47	45	43	49	46	44	42	47	45	43	42	41
				2 . 5	52	50	47	46	52	49	47	45	50	48	46	45	49	47	46	44	43
取付 高さ	器具間隔最大限		3 . 0	54	51	49	47	53	51	49	47	51	50	48	47	50	49	47	46	45	
	横方向 (A)	縦方向 (B)		4 . 0	55	53	51	50	54	53	51	50	53	51	50	49	51	50	49	48	47
H m	1 . 04 H m	1 . 04 H m		5 . 0	56	54	53	52	55	54	52	51	54	52	51	50	52	51	50	48	
				7 . 0	57	56	55	54	56	55	54	53	55	54	53	52	53	53	52	51	50
				10 . 0	57	57	56	55	57	56	55	55	55	55	54	54	54	54	53	53	51

