

屋内照明器具特性	
品番 (品名)	L R D 9 1 0 1
光源	L L D 3 0 2 0 M L C B 1 × 1 7 1 5 . 0 l m
管理番号	K 0 1 7 5 9 7 6 (0) D R 1
B Z 分類	B Z 1

器具効率		5 3 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		0 %	室指数	照明率 (X 0 . 0 1) Z C M																		0 %	
下方光束		5 3 %																					
保守率		良	0 . 6 3	0 . 6	4 4	4 0	3 8	3 7	4 3	4 0	3 8	3 7	4 2	4 0	3 8	3 6	4 2	3 9	3 8	3 6	3 6		
		中	0 . 6	0 . 8	4 7	4 4	4 2	4 0	4 6	4 4	4 2	4 0	4 6	4 3	4 1	4 0	4 5	4 3	4 1	4 0	3 9		
		否	1 . 0	4 9	4 6	4 4	4 3	4 8	4 6	4 4	4 3	4 8	4 5	4 4	4 3	4 7	4 5	4 3	4 2	4 2			
			0 . 5 6	1 . 2 5	5 1	4 8	4 7	4 5	5 0	4 8	4 6	4 5	4 9	4 7	4 6	4 5	4 8	4 7	4 5	4 4	4 4		
下方投影面積		c m ²		1 . 5	5 2	5 0	4 8	4 7	5 1	4 9	4 8	4 7	5 0	4 9	4 7	4 6	4 9	4 8	4 7	4 6	4 5		
等価発光面積		c m ²		2 . 0	5 3	5 1	5 0	4 9	5 3	5 1	5 0	4 9	5 2	5 0	4 9	4 8	5 1	5 0	4 9	4 8	4 7		
取付 高さ	器具間隔最大限		2 . 5	5 4	5 3	5 1	5 0	5 3	5 2	5 1	5 0	5 2	5 1	5 0	5 0	5 1	5 0	5 0	4 9	4 8			
	横方向 (A)	縦方向 (B)	3 . 0	5 5	5 3	5 2	5 1	5 4	5 3	5 2	5 1	5 3	5 2	5 1	5 0	5 2	5 1	5 0	5 0	4 9			
H m	0 . 4 1 H m	0 . 4 1 H m	4 . 0	5 5	5 4	5 3	5 3	5 5	5 4	5 3	5 2	5 4	5 3	5 2	5 2	5 3	5 2	5 1	5 1	5 0			
			5 . 0	5 6	5 5	5 4	5 4	5 5	5 4	5 4	5 3	5 4	5 3	5 3	5 2	5 3	5 2	5 2	5 2	5 0			
			7 . 0	5 6	5 6	5 5	5 5	5 6	5 5	5 5	5 4	5 4	5 4	5 4	5 3	5 3	5 3	5 3	5 2	5 1			
			1 0 . 0	5 7	5 6	5 6	5 5	5 6	5 6	5 5	5 5	5 5	5 4	5 4	5 4	5 4	5 3	5 3	5 3	5 1			

