

屋内照明器具特性	
品番 (品名)	L R D 9 2 0 2
光源	L L D 3 0 2 0 L C B 1 × 1 7 9 5 . 0 l m
管理番号	K 0 1 7 5 9 8 6 (0) D R 1
B Z 分類	B Z 1

器具効率		53 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束		0 %		床	10 %				10 %				10 %				10 %				0 %
下方光束		53 %	室指数	照明率 (X0.01) ZCM																	
保守率		良	0.63	0.6	44	40	38	37	43	40	38	37	43	40	38	37	42	40	38	37	36
		中	0.6	0.8	47	44	42	41	47	44	42	41	46	43	42	40	45	43	41	40	40
		否	1.0	49	47	45	43	49	46	44	43	48	46	44	43	47	45	44	43	42	
		0.56	1.25	51	49	47	45	50	48	47	45	49	48	46	45	49	47	46	45	44	
下方投影面積		c m ²	1.5	52	50	48	47	52	50	48	47	51	49	48	47	50	48	47	46	45	
等価発光面積			c m ²	2.0	54	52	50	49	53	51	50	49	52	51	50	49	51	50	49	48	47
取付	器具間隔最大限			2.5	54	53	52	51	54	52	51	50	53	52	51	50	52	51	50	49	48
高さ	横方向 (A)		縦方向 (B)	3.0	55	54	53	52	54	53	52	51	53	52	51	51	52	51	51	50	49
H m	0.41 H m		0.41 H m	4.0	56	55	54	53	55	54	53	53	54	53	53	52	53	52	52	51	50
				5.0	56	55	55	54	55	55	54	53	54	54	53	53	53	53	52	52	51
				7.0	57	56	55	55	56	55	55	54	55	54	54	54	54	53	53	53	51
				10.0	57	56	56	56	56	56	56	55	55	55	54	54	54	54	53	53	52

