

屋内照明器具特性	
品番 (品名)	L R D 9 2 0 2
光源	L L D 2 0 0 0 L C T 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 9 0 4 7 8 (0) D R 1
B Z 分類	B Z 3

器具効率		5 4 %		反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
					壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
					室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 3	0 . 6	3 3	2 8	2 4	2 1	3 3	2 7	2 4	2 1	3 2	2 7	2 3	2 1	3 1	2 6	2 3	2 1	2 0	
			0 . 6	0 . 8	3 9	3 4	3 0	2 7	3 8	3 3	3 0	2 7	3 7	3 3	3 0	2 7	3 6	3 2	2 9	2 7	2 6	
			0 . 5 6	1 . 0	4 3	3 8	3 4	3 2	4 2	3 7	3 4	3 2	4 0	3 7	3 4	3 2	3 9	3 6	3 3	3 1	3 0	
				1 . 2 5	4 6	4 1	3 8	3 6	4 5	4 1	3 8	3 6	4 3	4 0	3 7	3 5	4 2	3 9	3 7	3 5	3 4	
下方投影面積 等価発光面積		c m ² c m ²		1 . 5	4 8	4 4	4 1	3 9	4 7	4 3	4 1	3 8	4 5	4 2	4 0	3 8	4 4	4 2	4 0	3 8	3 7	
				2 . 0	5 0	4 7	4 5	4 3	4 9	4 7	4 4	4 2	4 8	4 6	4 4	4 2	4 7	4 5	4 3	4 1	4 0	
				2 . 5	5 2	4 9	4 7	4 5	5 1	4 9	4 7	4 5	5 0	4 8	4 6	4 4	4 8	4 7	4 5	4 4	4 3	
取付 高さ	器具間隔最大限			3 . 0	5 3	5 1	4 9	4 7	5 2	5 0	4 8	4 7	5 1	4 9	4 8	4 6	4 9	4 8	4 7	4 6	4 4	
	横方向 (A)	縦方向 (B)		4 . 0	5 4	5 2	5 1	5 0	5 3	5 2	5 0	4 9	5 2	5 1	5 0	4 8	5 1	5 0	4 9	4 8	4 6	
H m	1 . 2 1 H m	1 . 2 1 H m		5 . 0	5 5	5 4	5 2	5 1	5 4	5 3	5 2	5 1	5 3	5 2	5 1	5 0	5 2	5 1	5 0	4 9	4 8	
				7 . 0	5 6	5 5	5 4	5 3	5 5	5 4	5 3	5 2	5 4	5 3	5 2	5 2	5 3	5 2	5 1	5 1	4 9	
				1 0 . 0	5 6	5 6	5 5	5 4	5 6	5 5	5 4	5 4	5 5	5 4	5 3	5 3	5 3	5 3	5 2	5 2	5 0	

