

# 屋内照明器具特性

|         |                   |  |          |  |  |
|---------|-------------------|--|----------|--|--|
| 品番 (品名) | LGW71690          |  |          |  |  |
| 光源      | LED5000_70_485 x1 |  | 485.0 lm |  |  |
| 管理番号    | K0148420(0)DB1    |  |          |  |  |
| BZ分類    | BZ5/0.7/BZ4       |  |          |  |  |

|        |                 |         |      |     |     |     |     |     |     |     |     |     |     |    |     |     |    |    |    |     |
|--------|-----------------|---------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|-----|----|----|----|-----|
| 器具効率   | 100%            | 天井      | 80%  |     |     |     | 70% |     |     |     | 50% |     |     |    | 30% |     |    |    | 0% |     |
|        | 上方光束<br>0%      |         | 壁    | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30 | 10  | 70  | 50 | 30 | 10 | 0%  |
| 下方光束   | 100%            | 床       |      | 10% |     |     |     | 10% |     |     |     | 10% |     |    |     | 10% |    |    |    | 0%  |
| 室指数    | 照明率 ( X0.01 )   |         |      |     |     |     |     |     |     |     |     |     |     |    |     |     |    |    |    | ZCM |
| 保守率    | 良               | 0.69    | 0.6  | 58  | 46  | 39  | 34  | 57  | 46  | 39  | 33  | 55  | 45  | 38 | 33  | 53  | 44 | 38 | 33 | 31  |
|        | 中               | 0.67    | 0.8  | 68  | 57  | 50  | 44  | 67  | 57  | 49  | 44  | 64  | 55  | 49 | 44  | 62  | 54 | 48 | 44 | 42  |
|        | 否               | 0.63    | 1.0  | 75  | 65  | 57  | 52  | 74  | 64  | 57  | 52  | 71  | 62  | 56 | 51  | 68  | 61 | 55 | 51 | 49  |
|        |                 |         | 1.25 | 81  | 72  | 65  | 60  | 79  | 71  | 65  | 59  | 77  | 69  | 64 | 59  | 74  | 68 | 63 | 59 | 56  |
| 下方投影面積 | cm <sup>2</sup> |         | 1.5  | 85  | 77  | 71  | 65  | 84  | 76  | 70  | 65  | 81  | 74  | 69 | 65  | 78  | 72 | 68 | 64 | 62  |
| 等価発光面積 | cm <sup>2</sup> |         | 2.0  | 91  | 84  | 79  | 74  | 89  | 83  | 78  | 74  | 86  | 81  | 77 | 73  | 84  | 79 | 75 | 72 | 70  |
| 取付高さ   | 器具間隔最大限         |         | 2.5  | 94  | 89  | 84  | 80  | 93  | 87  | 83  | 79  | 90  | 85  | 82 | 78  | 87  | 83 | 80 | 77 | 75  |
|        | 横方向 (A)         | 縦方向 (B) | 3.0  | 97  | 92  | 87  | 84  | 95  | 91  | 87  | 83  | 92  | 89  | 85 | 82  | 90  | 87 | 84 | 81 | 79  |
| Hm     | 1.22Hm          | 1.22Hm  | 4.0  | 100 | 96  | 92  | 89  | 98  | 95  | 91  | 89  | 95  | 92  | 90 | 87  | 93  | 90 | 88 | 86 | 83  |
|        |                 |         | 5.0  | 101 | 98  | 95  | 93  | 100 | 97  | 94  | 92  | 97  | 95  | 93 | 91  | 95  | 93 | 91 | 89 | 86  |
|        |                 |         | 7.0  | 103 | 101 | 99  | 97  | 102 | 100 | 98  | 96  | 99  | 98  | 96 | 94  | 97  | 95 | 94 | 93 | 90  |
|        |                 |         | 10.0 | 105 | 103 | 102 | 100 | 103 | 102 | 100 | 99  | 101 | 100 | 98 | 97  | 99  | 98 | 97 | 96 | 93  |

