

屋内照明器具特性	
品番 (品名)	XAD1135L
光源	LED2700_70_430 ×1 430.0 l m
管理番号	K0165506 (1) DB 1
B Z 分類	BZ1

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		1 0 0 %																					
保守率		良 中 否	0 . 6 7	0 . 6	8 3	7 7	7 3	7 1	8 3	7 7	7 3	7 0	8 1	7 6	7 3	7 0	8 0	7 6	7 2	7 0	6 9		
			0 . 6 3	0 . 8	8 9	8 4	8 0	7 7	8 9	8 3	8 0	7 7	8 7	8 3	7 9	7 7	8 6	8 2	7 9	7 7	7 6		
			0 . 5 6	1 . 0	9 3	8 8	8 5	8 2	9 2	8 8	8 4	8 2	9 0	8 7	8 4	8 1	8 9	8 6	8 3	8 1	8 0		
				1 . 2 5	9 6	9 2	8 9	8 6	9 5	9 1	8 8	8 6	9 3	9 0	8 7	8 5	9 2	8 9	8 7	8 5	8 3		
下方投影面積		c m ²	1 . 5	9 8	9 4	9 1	8 9	9 7	9 4	9 1	8 9	9 5	9 2	9 0	8 8	9 4	9 1	8 9	8 7	8 6			
			等価発光面積		c m ²	2 . 0	1 0 1	9 8	9 5	9 3	1 0 0	9 7	9 4	9 3	9 8	9 5	9 3	9 2	9 6	9 4	9 2	9 1	8 9
取付 高さ	器具間隔最大限		2 . 5	1 0 2	1 0 0	9 7	9 6	1 0 1	9 9	9 7	9 5	9 9	9 7	9 5	9 4	9 7	9 6	9 4	9 3	9 1			
	横方向 (A)		縦方向 (B)		3 . 0	1 0 3	1 0 1	9 9	9 7	1 0 2	1 0 0	9 8	9 7	1 0 0	9 8	9 7	9 6	9 8	9 7	9 6	9 4	9 2	
H m	0 . 4 0 H m		0 . 4 0 H m		4 . 0	1 0 5	1 0 3	1 0 1	1 0 0	1 0 3	1 0 2	1 0 0	9 9	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 4	
					5 . 0	1 0 5	1 0 4	1 0 3	1 0 1	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 8	9 5	
					7 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 1	1 0 1	1 0 0	1 0 0	9 9	9 6	
					1 0 . 0	1 0 7	1 0 6	1 0 5	1 0 5	1 0 6	1 0 5	1 0 4	1 0 4	1 0 3	1 0 3	1 0 2	1 0 2	1 0 1	1 0 1	1 0 0	1 0 0	9 7	

