

屋内照明器具特性	
品番 (品名)	XAD1435L
光源	LED2700_70_400 ×1 400.0 l m
管理番号	K0166927 (1) D 1
BZ分類	BZ1

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
上方光束		0 %	室指数	床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
下方光束		1 0 0 %		照明率 (X 0 . 0 1) Z C M																	
保守率		良	0 . 6 7	0 . 6	8 3	7 6	7 2	6 9	8 2	7 6	7 2	6 9	8 0	7 5	7 2	6 9	7 9	7 5	7 1	6 9	6 8
		中	0 . 6 3	0 . 8	8 8	8 3	7 9	7 6	8 8	8 2	7 9	7 6	8 6	8 1	7 8	7 6	8 5	8 1	7 8	7 5	7 4
		否	0 . 5 6	1 . 0	9 2	8 7	8 3	8 0	9 1	8 6	8 3	8 0	8 9	8 5	8 2	8 0	8 8	8 4	8 2	7 9	7 8
				1 . 2 5	9 5	9 1	8 7	8 4	9 4	9 0	8 7	8 4	9 2	8 9	8 6	8 4	9 1	8 8	8 5	8 3	8 2
下方投影面積		c m ²		1 . 5	9 7	9 3	9 0	8 7	9 6	9 2	8 9	8 7	9 4	9 1	8 9	8 6	9 3	9 0	8 8	8 6	8 4
等価発光面積		c m ²		2 . 0	1 0 0	9 7	9 4	9 1	9 9	9 6	9 3	9 1	9 7	9 4	9 2	9 0	9 5	9 3	9 1	8 9	8 8
取付 高さ	器具間隔最大限			2 . 5	1 0 2	9 9	9 6	9 4	1 0 1	9 8	9 6	9 4	9 8	9 6	9 4	9 3	9 6	9 5	9 3	9 2	9 0
	横方向 (A)		縦方向 (B)	3 . 0	1 0 3	1 0 0	9 8	9 6	1 0 2	9 9	9 7	9 6	9 9	9 8	9 6	9 4	9 7	9 6	9 5	9 3	9 1
H m	0 . 4 1 H m		0 . 4 1 H m	4 . 0	1 0 4	1 0 2	1 0 0	9 9	1 0 3	1 0 1	1 0 0	9 8	1 0 1	9 9	9 8	9 7	9 9	9 8	9 6	9 5	9 3
				5 . 0	1 0 5	1 0 3	1 0 2	1 0 0	1 0 4	1 0 2	1 0 1	1 0 0	1 0 2	1 0 0	9 9	9 8	1 0 0	9 9	9 8	9 7	9 4
				7 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 0	1 0 0	1 0 0	9 9	9 8	9 6
				1 0 . 0	1 0 7	1 0 6	1 0 5	1 0 4	1 0 5	1 0 5	1 0 4	1 0 3	1 0 3	1 0 3	1 0 2	1 0 1	1 0 1	1 0 1	1 0 0	1 0 0	9 7

