

屋内照明器具特性	
品番 (品名)	L G S 9 0 0 2
光源	LLD4000LCS1 ×1 830.0 l m
管理番号	K0183281 (0) DR 1
B Z 分類	B Z 4

器具効率		75 % 0 % 75 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.67	0.6	45	36	31	27	44	36	31	27	42	35	30	27	41	34	30	27	25
			0.63	0.8	52	44	39	35	51	44	39	35	49	43	38	35	48	42	38	34	33
			0.56	1.0	57	50	45	41	56	49	44	41	54	48	44	40	52	47	43	40	38
				1.25	61	55	50	46	60	54	50	46	58	53	49	46	56	52	48	45	44
下方投影面積 等価発光面積		c m ² c m ²		1.5	64	58	54	50	63	58	53	50	61	56	53	49	59	55	52	49	47
				2.0	68	63	59	56	67	63	59	56	65	61	58	55	63	60	57	55	53
				2.5	71	67	63	60	70	66	62	60	67	64	61	59	66	63	60	58	56
				3.0	72	69	66	63	71	68	65	63	69	66	64	62	67	65	63	61	59
H m	1.27 H m	1.27 H m		4.0	74	72	69	67	73	71	68	66	71	69	67	65	69	68	66	64	62
				5.0	76	73	71	69	75	73	71	69	73	71	69	68	71	69	68	67	65
				7.0	77	75	74	72	76	75	73	72	74	73	72	70	72	71	70	69	67
				10.0	78	77	76	75	77	76	75	74	75	74	74	73	74	73	72	71	69

