

屋内照明器具特性	
品番 (品名)	L G S 9 0 0 2
光源	LLD40402CQ1 (KAKUSAN) ×1 860.0 l m
管理番号	K0184328 (0) DR 1
B Z 分類	BZ4 / 0.7 / BZ3 / 1.8 / BZ4

器具効率		71 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.67	0.6	43	35	30	27	42	35	30	27	41	34	30	27	39	34	29	26	25
			0.63	0.8	50	43	38	34	49	43	38	34	48	42	37	34	46	41	37	34	33
			0.56	1.0	55	48	43	40	54	48	43	40	52	47	43	39	50	46	42	39	38
				1.25	59	53	48	45	58	52	48	45	56	51	47	44	54	50	47	44	43
下方投影面積		cm ²		1.5	62	56	52	49	61	56	52	49	59	54	51	48	57	53	50	48	46
				2.0	65	61	57	54	64	60	57	54	62	59	56	53	60	57	55	53	51
等価発光面積		cm ²		2.5	68	64	61	58	66	63	60	57	65	62	59	57	63	60	58	56	54
				3.0	69	66	63	60	68	65	62	60	66	64	61	59	64	62	60	59	57
H m	1.26 H m		1.26 H m	4.0	71	68	66	64	70	68	65	64	68	66	64	63	66	65	63	62	60
				5.0	72	70	68	66	71	69	67	66	69	68	66	65	68	66	65	64	62
				7.0	73	72	70	69	72	71	70	68	71	69	68	67	69	68	67	66	64
				10.0	74	73	72	71	73	72	71	70	72	71	70	69	70	69	69	68	66

