

屋内照明器具特性	
品番 (品名)	L G S 9 0 0 4
光源	L L D 3 0 2 0 M L C B 1 × 1 7 1 5 . 0 l m
管理番号	K 0 1 7 9 4 8 2 (0) D R 1
B Z 分類	B Z 1

器具効率		9 4 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		1 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		9 3 %																				
保守率		良	0 . 6 7	0 . 6	7 8	7 3	6 9	6 6	7 8	7 2	6 9	6 6	7 6	7 2	6 8	6 6	7 5	7 1	6 8	6 6	6 5	
		中	0 . 6 3	0 . 8	8 4	7 9	7 5	7 3	8 3	7 8	7 5	7 2	8 1	7 7	7 4	7 2	8 0	7 7	7 4	7 2	7 1	
		否	0 . 5 6	1 . 0	8 7	8 3	7 9	7 7	8 6	8 2	7 9	7 6	8 5	8 1	7 8	7 6	8 3	8 0	7 8	7 6	7 4	
				1 . 2 5	9 0	8 6	8 3	8 0	8 9	8 5	8 2	8 0	8 7	8 4	8 2	8 0	8 6	8 3	8 1	7 9	7 8	
下方投影面積		c m ²		1 . 5	9 2	8 8	8 5	8 3	9 1	8 7	8 5	8 3	8 9	8 6	8 4	8 2	8 7	8 5	8 3	8 1	8 0	
等価発光面積		c m ²		2 . 0	9 4	9 1	8 9	8 7	9 3	9 0	8 8	8 6	9 1	8 9	8 7	8 5	8 9	8 7	8 6	8 4	8 3	
取付 高さ	器具間隔最大限		2 . 5	9 6	9 3	9 1	8 9	9 5	9 2	9 0	8 9	9 3	9 1	8 9	8 7	9 1	8 9	8 8	8 6	8 5		
	横方向 (A)	縦方向 (B)	3 . 0	9 7	9 4	9 2	9 1	9 5	9 3	9 2	9 0	9 3	9 2	9 0	8 9	9 1	9 0	8 9	8 8	8 6		
H m	0 . 4 1 H m	0 . 4 1 H m	4 . 0	9 8	9 6	9 4	9 3	9 7	9 5	9 4	9 2	9 5	9 3	9 2	9 1	9 3	9 2	9 1	9 0	8 7		
			5 . 0	9 8	9 7	9 6	9 5	9 7	9 6	9 5	9 4	9 5	9 4	9 3	9 2	9 3	9 2	9 2	9 1	8 8		
			7 . 0	9 9	9 8	9 7	9 6	9 8	9 7	9 6	9 5	9 6	9 5	9 4	9 4	9 4	9 3	9 3	9 2	9 0		
			1 0 . 0	1 0 0	9 9	9 8	9 8	9 9	9 8	9 7	9 7	9 7	9 6	9 5	9 5	9 5	9 4	9 4	9 3	9 1		

