

屋内照明器具特性	
品番 (品名)	L G S 9 0 0 4
光源	LLD40402CQ1 (KAKUSAN) ×1 860.0 l m
管理番号	K0184332 (0) DR 1
B Z 分類	BZ4 / 3.5 / BZ5

器具効率		78 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		12 %	室指数	照明率 (X0.01)																			Z	C	M
下方光束		66 %																							
保守率		良 中 否	0.67	0.6	45	36	30	26	43	35	30	26	40	33	29	25	38	32	28	25	22				
			0.63	0.8	52	44	38	34	50	43	37	34	47	41	36	32	44	38	35	31	29				
			0.56	1.0	57	49	44	40	55	48	43	39	51	45	41	38	48	43	39	36	33				
				1.25	61	54	49	45	59	53	48	44	55	50	46	42	52	47	44	41	38				
下方投影面積		cm ²	1.5	64	58	53	49	62	56	52	48	58	53	49	46	54	50	47	44	41					
等価発光面積			2.0	68	63	58	55	66	61	57	53	62	58	54	51	58	54	52	49	45					
取付 高さ	器具間隔最大限		2.5	70	66	62	58	68	64	60	57	64	60	57	55	60	57	55	52	48					
	横方向 (A) 縦方向 (B)		3.0	72	68	64	61	70	66	63	60	66	62	60	57	62	59	57	55	51					
H m	1.22 H m	1.22 H m	4.0	74	71	68	65	72	69	66	64	68	65	63	61	64	62	60	58	54					
			5.0	76	73	70	68	73	71	68	66	69	67	65	63	65	63	62	60	55					
			7.0	77	75	73	71	75	73	71	70	71	69	68	66	67	65	64	63	58					
			10.0	78	77	75	74	76	75	73	72	72	71	70	69	68	67	66	65	60					

