

屋内照明器具特性	
品番 (品名)	LGS9502
光源	LLD3020LCB1 ×1 795.0 l m
管理番号	K0179476 (0) DR 1
B Z 分類	BZ1

器具効率		87 %	反射率	天井	80 %				70 %				50 %				30 %				0 %						
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %						
				床	10 %				10 %				10 %				10 %				0 %						
上方光束		0 %	室指数	照明率 (X0.01)																				Z	C		M
下方光束		87 %																									
保守率		良 中 否	0.67	0.6	73	67	64	62	72	67	64	62	71	67	64	62	70	66	63	62	61						
			0.63	0.8	78	73	70	68	77	73	70	67	76	72	69	67	75	71	69	67	66						
			0.56	1.0	81	77	74	71	80	76	73	71	79	75	73	71	77	75	72	71	70						
			1.25	84	80	77	75	83	79	77	75	81	78	76	74	80	77	75	74	73							
下方投影面積		c m ²	1.5	85	82	79	77	84	81	79	77	83	80	78	77	81	79	77	76	75							
			2.0	87	85	83	81	87	84	82	80	85	83	81	80	83	82	80	79	77							
取付高さ	器具間隔最大限		2.5	89	87	85	83	88	86	84	83	86	84	83	82	85	83	82	81	79							
	横方向 (A)	縦方向 (B)	3.0	90	88	86	85	89	87	85	84	87	85	84	83	85	84	83	82	80							
H m	0.41 H m	0.41 H m	4.0	91	89	88	87	90	88	87	86	88	87	86	85	86	85	84	84	82							
			5.0	91	90	89	88	90	89	88	87	89	88	87	86	87	86	85	85	83							
			7.0	92	91	90	90	91	90	90	89	89	89	88	87	87	87	86	86	84							
			10.0	93	92	91	91	92	91	91	90	90	89	89	88	88	88	87	87	85							

