

# 屋内照明器具特性

|         |                   |          |
|---------|-------------------|----------|
| 品番 (品名) | LSEB5800          |          |
| 光源      | LED5000_70_460 x1 | 460.0 lm |
| 管理番号    | K0151698(0)D 1    |          |
| BZ分類    | BZ3               |          |

| 器具効率   | 100%     | 天井               | 80%  |               |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |    |    | 0% |    |  |  |  |
|--------|----------|------------------|------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|----|--|--|--|
|        |          |                  | 壁    | 70            | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50 | 30 | 10 | 0% |  |  |  |
| 上方光束   | 0%       | 反射率              | 床    | 10%           |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |    |    |    | 0% |  |  |  |
| 下方光束   | 100%     |                  | 室指数  | 照明率 ( X0.01 ) |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |    |  |  |  |
| 保守率    | 良        | 0.67             | 0.6  | 64            | 54  | 47  | 42  | 63  | 53  | 47  | 42  | 61  | 52  | 47  | 42  | 59  | 51 | 46 | 42 | 40 |  |  |  |
|        | 中        | 0.63             | 0.8  | 74            | 65  | 58  | 54  | 73  | 64  | 58  | 54  | 71  | 63  | 58  | 53  | 69  | 62 | 57 | 53 | 51 |  |  |  |
|        | 否        | 0.56             | 1.0  | 81            | 72  | 66  | 62  | 80  | 72  | 66  | 61  | 77  | 70  | 65  | 61  | 75  | 69 | 64 | 61 | 59 |  |  |  |
|        |          |                  | 1.25 | 86            | 79  | 73  | 69  | 85  | 78  | 73  | 68  | 82  | 76  | 72  | 68  | 80  | 75 | 71 | 67 | 66 |  |  |  |
| 下方投影面積 | 等価発光面積   | c m <sup>2</sup> | 1.5  | 90            | 83  | 78  | 74  | 88  | 82  | 77  | 73  | 86  | 81  | 76  | 73  | 83  | 79 | 75 | 72 | 70 |  |  |  |
|        |          |                  | 2.0  | 94            | 89  | 84  | 81  | 93  | 88  | 84  | 80  | 90  | 86  | 83  | 79  | 88  | 84 | 81 | 79 | 77 |  |  |  |
| 取付高さ   | 器具間隔最大限  |                  | 2.5  | 97            | 93  | 89  | 85  | 96  | 92  | 88  | 85  | 93  | 90  | 87  | 84  | 91  | 88 | 85 | 83 | 81 |  |  |  |
|        | 横方向 (A)  | 縦方向 (B)          | 3.0  | 99            | 95  | 92  | 89  | 98  | 94  | 91  | 88  | 95  | 92  | 89  | 87  | 93  | 90 | 88 | 86 | 83 |  |  |  |
| H m    | 1.15 H m | 1.15 H m         | 4.0  | 101           | 98  | 95  | 93  | 100 | 97  | 95  | 92  | 98  | 95  | 93  | 91  | 95  | 93 | 91 | 90 | 87 |  |  |  |
|        |          |                  | 5.0  | 103           | 100 | 98  | 96  | 102 | 99  | 97  | 95  | 99  | 97  | 95  | 94  | 97  | 95 | 94 | 92 | 90 |  |  |  |
|        |          |                  | 7.0  | 104           | 102 | 101 | 99  | 103 | 101 | 100 | 98  | 101 | 99  | 98  | 97  | 98  | 97 | 96 | 95 | 92 |  |  |  |
|        |          |                  | 10.0 | 106           | 104 | 103 | 102 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 99  | 100 | 99 | 98 | 97 | 94 |  |  |  |

