

屋内照明器具特性	
品番 (品名)	L G S 9 5 0 3
光源	L L D 2 0 0 0 L C S 1 × 1 5 8 0 . 0 l m
管理番号	K 0 1 8 3 2 8 5 (0) D R 1
B Z 分類	B Z 3

器具効率		53 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束 下方光束		0 % 53 %	室指数	照明率 (X0.01) ZCM																	
保守率		良 中 否	0.67	0.6	33	27	24	21	33	27	24	21	31	27	23	21	30	26	23	21	20
			0.63	0.8	39	33	30	27	38	33	29	27	37	32	29	27	35	32	29	27	26
			1.0	42	37	34	31	41	37	33	31	40	36	33	31	39	35	33	30	29	
			0.56	1.25	45	41	37	35	44	40	37	35	43	39	37	34	41	38	36	34	33
下方投影面積		cm ²	1.5	47	43	40	38	46	43	40	37	45	42	39	37	43	41	39	37	36	
等価発光面積		cm ²	2.0	50	46	44	42	49	46	43	41	47	45	43	41	46	44	42	40	39	
取付 高さ	器具間隔最大限		2.5	51	48	46	44	50	48	46	44	49	47	45	43	48	46	44	43	42	
	横方向 (A) 縦方向 (B)		3.0	52	50	48	46	51	49	47	46	50	48	47	45	49	47	46	45	43	
H m	1.18 H m	1.18 H m	4.0	54	52	50	49	53	51	50	48	52	50	49	48	50	49	48	47	46	
			5.0	54	53	52	50	54	52	51	50	52	51	50	49	51	50	49	48	47	
			7.0	55	54	53	52	55	54	53	52	53	52	52	51	52	51	51	50	49	
			10.0	56	55	55	54	55	55	54	53	54	53	53	52	53	52	52	51	50	

