

屋内照明器具特性	
品番 (品名)	L G S 9 3 0 0
光源	L L D 2 0 0 0 L C S 1 × 2 5 8 0 . 0 l m
管理番号	K 0 1 8 3 2 8 2 (0) D R 1
B Z 分類	B Z 4

器具効率		5 7 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
						室指数	照明率 (X 0 . 0 1) Z C M															
保守率		良 中 否	0 . 6 7	0 . 6	3 4	2 7	2 3	2 0	3 3	2 7	2 3	2 0	3 2	2 6	2 3	2 0	3 1	2 6	2 3	2 0	1 9	
			0 . 6 3	0 . 8	4 0	3 4	2 9	2 6	3 9	3 3	2 9	2 6	3 7	3 2	2 9	2 6	3 6	3 2	2 9	2 6	2 5	
			0 . 5 6	1 . 0	4 3	3 8	3 4	3 1	4 2	3 7	3 4	3 1	4 1	3 6	3 3	3 0	3 9	3 6	3 3	3 0	2 9	
				1 . 2 5	4 7	4 2	3 8	3 5	4 6	4 1	3 8	3 5	4 4	4 0	3 7	3 5	4 3	3 9	3 6	3 4	3 3	
下方投影面積		c m ²	1 . 5	4 9	4 4	4 1	3 8	4 8	4 4	4 0	3 8	4 6	4 3	4 0	3 7	4 5	4 2	3 9	3 7	3 6		
			等価発光面積	c m ²	2 . 0	5 2	4 8	4 5	4 2	5 1	4 7	4 5	4 2	4 9	4 6	4 4	4 2	4 8	4 5	4 3	4 1	4 0
取付 高さ	器具間隔最大限		2 . 5	5 4	5 0	4 8	4 5	5 3	5 0	4 7	4 5	5 1	4 9	4 6	4 5	5 0	4 8	4 6	4 4	4 3		
	横方向 (A) 縦方向 (B)		3 . 0	5 5	5 2	5 0	4 8	5 4	5 1	4 9	4 7	5 2	5 0	4 8	4 7	5 1	4 9	4 8	4 6	4 5		
H m	1 . 2 7 H m	1 . 2 7 H m	4 . 0	5 6	5 4	5 2	5 1	5 6	5 4	5 2	5 0	5 4	5 2	5 1	4 9	5 3	5 1	5 0	4 9	4 7		
			5 . 0	5 7	5 6	5 4	5 2	5 7	5 5	5 3	5 2	5 5	5 4	5 2	5 1	5 4	5 3	5 1	5 0	4 9		
			7 . 0	5 8	5 7	5 6	5 5	5 8	5 6	5 5	5 4	5 6	5 5	5 4	5 3	5 5	5 4	5 3	5 2	5 1		
			1 0 . 0	5 9	5 8	5 7	5 7	5 9	5 8	5 7	5 6	5 7	5 6	5 6	5 5	5 6	5 5	5 5	5 4	5 2		

