

屋内照明器具特性	
品番 (品名)	LGS9302
光源	LLD3020LCB1 x2 795.0 lm
管理番号	K0179481 (0) DR1
BZ分類	BZ1

器具効率		88 %	反射率	天井	80 %				70 %				50 %				30 %				0 %						
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %						
				床	10 %				10 %				10 %				10 %				0 %						
上方光束		0 %	室指数	照明率 (X0.01)																				Z	C		M
下方光束		88 %																									
保守率		良 中 否	0.67	0.6	74	68	65	62	73	68	65	62	72	67	64	62	71	67	64	62	61						
			0.63	0.8	79	74	71	68	78	73	70	68	77	73	70	68	75	72	69	68	66						
			0.56	1.0	82	78	74	72	81	77	74	72	79	76	73	71	78	75	73	71	70						
			1.25	84	81	78	76	84	80	77	75	82	79	77	75	80	78	76	74	73							
下方投影面積		c m ²	1.5	86	83	80	78	85	82	80	78	84	81	79	77	82	80	78	76	75							
			2.0	88	86	83	81	87	85	83	81	86	84	82	80	84	82	81	79	78							
取付高さ	器具間隔最大限		2.5	90	87	85	84	89	87	85	83	87	85	84	82	85	84	82	81	79							
	横方向 (A)	縦方向 (B)	3.0	91	89	87	85	90	88	86	85	88	86	85	84	86	85	84	83	81							
H m	0.41 H m	0.41 H m	4.0	92	90	89	87	91	89	88	87	89	88	86	85	87	86	85	84	82							
			5.0	92	91	90	89	91	90	89	88	89	88	88	87	88	87	86	85	83							
			7.0	93	92	91	90	92	91	90	90	90	89	89	88	88	88	87	87	84							
			10.0	94	93	92	92	93	92	92	91	91	90	90	89	89	88	88	88	85							

