

屋内照明器具特性	
品番 (品名)	XAS3030N
光源	LED5000_70_700 ×1 700.0 l m
管理番号	K0166827 (0) D 1
BZ分類	BZ1

器具効率 上方光束 下方光束	1 0 1 % 0 % 1 0 1 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
			壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
			床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
		室指数	照明率 (X 0 . 0 1) Z C M																		
保守率	良 中 否	0 . 6	8 2	7 6	7 2	6 9	8 1	7 5	7 1	6 9	8 0	7 5	7 1	6 8	7 9	7 4	7 1	6 8	6 7		
		0 . 6 3	8 8	8 2	7 8	7 5	8 7	8 2	7 8	7 5	8 6	8 1	7 8	7 5	8 4	8 0	7 7	7 5	7 3		
		1 . 0	9 2	8 7	8 3	8 0	9 1	8 6	8 2	8 0	8 9	8 5	8 2	7 9	8 8	8 4	8 1	7 9	7 8		
		0 . 5 6	1 . 2 5	9 5	9 0	8 7	8 4	9 4	9 0	8 6	8 4	9 2	8 9	8 6	8 3	9 1	8 7	8 5	8 3	8 1	
下方投影面積 等価発光面積	c m ² c m ²	1 . 5	9 7	9 3	9 0	8 7	9 6	9 2	8 9	8 7	9 4	9 1	8 8	8 6	9 3	9 0	8 7	8 6	8 4		
		2 . 0	1 0 0	9 7	9 4	9 1	9 9	9 6	9 3	9 1	9 7	9 4	9 2	9 0	9 5	9 3	9 1	8 9	8 7		
取付 高さ	器具間隔最大限		2 . 5	1 0 2	9 9	9 6	9 4	1 0 1	9 8	9 6	9 4	9 9	9 6	9 4	9 3	9 7	9 5	9 3	9 2	9 0	
	横方向 (A)	縦方向 (B)	3 . 0	1 0 3	1 0 0	9 8	9 6	1 0 2	1 0 0	9 7	9 6	1 0 0	9 8	9 6	9 4	9 8	9 6	9 5	9 3	9 1	
H m	0 . 4 1 H m	0 . 4 1 H m	4 . 0	1 0 5	1 0 2	1 0 1	9 9	1 0 3	1 0 1	1 0 0	9 8	1 0 1	1 0 0	9 8	9 7	9 9	9 8	9 7	9 6	9 3	
			5 . 0	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 3	1 0 1	1 0 0	1 0 2	1 0 1	1 0 0	9 8	1 0 0	9 9	9 8	9 7	9 5	
			7 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 9	9 6	
			1 0 . 0	1 0 7	1 0 6	1 0 5	1 0 5	1 0 6	1 0 5	1 0 4	1 0 4	1 0 4	1 0 3	1 0 2	1 0 2	1 0 2	1 0 1	1 0 0	1 0 0	9 7	

