

| 屋内照明器具特性 |                            |
|----------|----------------------------|
| 品番 (品名)  | XAD3104N                   |
| 光源       | LED5000_70_600 ×1 600.0 lm |
| 管理番号     | K0165490 ( 0 ) DB1         |
| BZ分類     | BZ4/0.7/BZ3                |

| 器具効率      |          | 100 %<br><br>上方光束<br>0 %<br>下方光束<br>100 % |                 | 反射率     | 天井  | 80 %              |     |     |     | 70 % |     |     |     | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|-----------|----------|-------------------------------------------|-----------------|---------|-----|-------------------|-----|-----|-----|------|-----|-----|-----|------|----|----|----|------|----|----|----|-----|
|           |          |                                           |                 |         | 壁   | 70                | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|           |          |                                           |                 |         | 床   | 10 %              |     |     |     | 10 % |     |     |     | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|           |          |                                           |                 | 室指数     |     | 照明率 ( X0.01 ) ZCM |     |     |     |      |     |     |     |      |    |    |    |      |    |    |    |     |
| 保守率       |          | 良<br>中<br>否                               | 0.67            | 0.6     | 61  | 50                | 43  | 37  | 60  | 49   | 42  | 37  | 58  | 48   | 42 | 37 | 56 | 47   | 41 | 37 | 35 |     |
|           |          |                                           | 0.63            | 0.8     | 72  | 61                | 54  | 49  | 70  | 61   | 54  | 49  | 68  | 59   | 53 | 49 | 65 | 58   | 53 | 49 | 47 |     |
|           |          |                                           | 1.0             | 78      | 69  | 62                | 57  | 77  | 68  | 62   | 57  | 74  | 67  | 61   | 57 | 72 | 65 | 60   | 56 | 54 |    |     |
|           |          |                                           | 0.56            | 1.25    | 84  | 76                | 70  | 65  | 83  | 75   | 69  | 65  | 80  | 74   | 68 | 64 | 78 | 72   | 68 | 64 | 62 |     |
| 下方投影面積    |          | cm <sup>2</sup>                           | 1.5             | 88      | 81  | 75                | 70  | 87  | 80  | 75   | 70  | 84  | 78  | 73   | 70 | 81 | 76 | 72   | 69 | 67 |    |     |
| 等価発光面積    |          |                                           | cm <sup>2</sup> | 2.0     | 93  | 87                | 82  | 78  | 92  | 86   | 82  | 78  | 89  | 84   | 80 | 77 | 87 | 83   | 79 | 76 | 74 |     |
| 取付高さ      |          |                                           |                 | 器具間隔最大限 |     | 2.5               | 96  | 91  | 87  | 83   | 95  | 90  | 86  | 83   | 92 | 88 | 85 | 82   | 90 | 86 | 83 | 81  |
| 横方向 ( A ) |          | 縦方向 ( B )                                 |                 | 3.0     | 98  | 94                | 90  | 87  | 97  | 93   | 89  | 86  | 94  | 91   | 88 | 85 | 92 | 89   | 86 | 84 | 82 |     |
| H m       | 1.25 H m | 1.25 H m                                  | 4.0             | 101     | 97  | 94                | 92  | 99  | 96  | 94   | 91  | 97  | 94  | 92   | 90 | 94 | 92 | 90   | 88 | 86 |    |     |
|           |          |                                           | 5.0             | 102     | 100 | 97                | 95  | 101 | 98  | 96   | 94  | 99  | 96  | 94   | 93 | 96 | 94 | 93   | 91 | 89 |    |     |
|           |          |                                           | 7.0             | 104     | 102 | 100               | 98  | 103 | 101 | 99   | 98  | 100 | 99  | 97   | 96 | 98 | 97 | 95   | 94 | 92 |    |     |
|           |          |                                           | 10.0            | 105     | 104 | 103               | 101 | 104 | 103 | 102  | 100 | 102 | 101 | 100  | 98 | 99 | 98 | 98   | 97 | 94 |    |     |

