

屋内照明器具特性	
品番 (品名)	XAS3501V
光源	LED3500_70_660 ×1 660.0 lm
管理番号	K0166825 (0) D 1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %					70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %					10 %				10 %				10 %				0 %				
上方光束		100 %	室指数	照明率 (X0.01)																			Z CM			
下方光束																										
保守率		良 中 否	0.67	0.6	57	45	37	32	56	44	37	32	54	43	37	32	51	42	36	32	30					
			0.63	0.8	67	56	48	42	66	55	48	42	63	54	47	42	61	52	46	42	40					
			0.56	1.0	74	63	56	50	72	62	55	50	69	61	54	49	67	59	54	49	47					
				1.25	80	70	63	58	78	69	63	57	75	68	62	57	73	66	61	56	54					
下方投影面積		cm ²	1.5	84	75	69	63	82	74	68	63	79	72	67	62	77	71	66	62	59						
等価発光面積			cm ²	2.0	90	82	77	72	88	81	76	71	85	79	75	70	82	77	73	70	67					
取付高さ	器具間隔最大限			2.5	93	87	82	77	92	86	81	77	89	84	80	76	86	82	78	75	72					
	横方向 (A)			縦方向 (B)		3.0	96	90	86	82	94	89	85	81	91	87	83	80	88	85	82	79	76			
H m	1.26 H m	1.26 H m		4.0	99	95	91	87	97	93	90	87	94	91	88	85	92	89	86	84	82					
			5.0	101	97	94	91	99	96	93	90	96	94	91	89	94	92	89	88	85						
			7.0	103	100	98	96	101	99	97	95	99	97	95	93	96	95	93	92	89						
			10.0	104	103	101	99	103	101	100	98	101	99	98	96	98	97	96	95	92						

