

屋内照明器具特性	
品番 (品名)	XAS3521V
光源	LED3500_70_660 ×1 660.0 l m
管理番号	K0166827 (0) D 1
B Z 分類	BZ1

器具効率		1 0 1 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																				Z C M
下方光束		1 0 1 %																						
保守率		良 中 否	0 . 6 7	0 . 6	8 2	7 6	7 2	6 9	8 1	7 5	7 1	6 9	8 0	7 5	7 1	6 8	7 9	7 4	7 1	6 8	6 7			
			0 . 6 3	0 . 8	8 8	8 2	7 8	7 5	8 7	8 2	7 8	7 5	8 6	8 1	7 8	7 5	8 4	8 0	7 7	7 5	7 3			
			0 . 5 6	1 . 0	9 2	8 7	8 3	8 0	9 1	8 6	8 2	8 0	8 9	8 5	8 2	7 9	8 8	8 4	8 1	7 9	7 8			
下方投影面積 等価発光面積		c m ² c m ²	1 . 2 5	9 5	9 0	8 7	8 4	9 4	9 0	8 6	8 4	9 2	8 9	8 6	8 3	9 1	8 7	8 5	8 3	8 1				
			1 . 5	9 7	9 3	9 0	8 7	9 6	9 2	8 9	8 7	9 4	9 1	8 8	8 6	9 3	9 0	8 7	8 6	8 4				
			2 . 0	1 0 0	9 7	9 4	9 1	9 9	9 6	9 3	9 1	9 7	9 4	9 2	9 0	9 5	9 3	9 1	8 9	8 7				
取付 高さ	器具間隔最大限		2 . 5	1 0 2	9 9	9 6	9 4	1 0 1	9 8	9 6	9 4	9 9	9 6	9 4	9 3	9 7	9 5	9 3	9 2	9 0				
	横方向 (A)	縦方向 (B)	3 . 0	1 0 3	1 0 0	9 8	9 6	1 0 2	1 0 0	9 7	9 6	1 0 0	9 8	9 6	9 4	9 8	9 6	9 5	9 3	9 1				
H m	0 . 4 1 H m	0 . 4 1 H m	4 . 0	1 0 5	1 0 2	1 0 1	9 9	1 0 3	1 0 1	1 0 0	9 8	1 0 1	1 0 0	9 8	9 7	9 9	9 8	9 7	9 6	9 3				
			5 . 0	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 3	1 0 1	1 0 0	1 0 2	1 0 1	1 0 0	9 8	1 0 0	9 9	9 8	9 7	9 5				
			7 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 9	9 6				
			1 0 . 0	1 0 7	1 0 6	1 0 5	1 0 5	1 0 6	1 0 5	1 0 4	1 0 4	1 0 4	1 0 3	1 0 2	1 0 2	1 0 2	1 0 1	1 0 0	1 0 0	9 7				

