

屋内照明器具特性	
品番 (品名)	S F 9 0 7
光源	LDA7L - G / Z60E / S / W / 2 × 1 810.0 l m
管理番号	K0157674 ( 0 ) DB 1
B Z 分類	BZ9 / 0.9 / BZ8

器具効率	93 %	天井	80 %				70 %				50 %				30 %				0 %			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
上方光束	63 %	床	10 %				10 %				10 %				10 %				0 %			
下方光束	30 %	室指数	照明率 ( X0.01 ) ZCM																			
保守率	良 0.63 中 0.6 否 0.56	0.6	41	30	23	18	36	26	20	16	28	21	16	12	20	15	11	9	3			
		0.8	48	38	30	25	43	34	27	23	33	26	21	18	24	19	16	13	5			
		1.0	54	44	36	31	48	39	33	28	37	31	26	22	27	23	19	16	7			
		1.25	59	49	42	37	52	44	38	33	41	35	30	26	30	26	22	20	9			
下方投影面積	c m <sup>2</sup>	1.5	62	54	47	41	56	48	42	38	44	38	34	30	32	28	25	22	11			
		2.0	67	60	54	49	60	54	49	44	47	43	39	35	35	32	29	26	13			
取付高さ	器具間隔最大限		2.5	71	64	59	54	64	58	53	49	50	46	42	39	37	34	32	15			
	横方向 (A)	縦方向 (B)	3.0	73	67	62	58	66	61	56	52	52	48	45	42	39	36	34	16			
H m	0.00 H m	0.00 H m	4.0	76	71	67	63	68	64	61	57	54	51	48	46	41	39	37	18			
			5.0	78	74	70	67	70	67	63	61	56	53	51	49	42	40	39	20			
			7.0	80	77	74	71	72	70	67	65	58	56	54	52	44	43	41	22			
			10.0	82	80	77	75	74	72	70	68	59	58	56	55	45	44	43	23			

