

屋内照明器具特性

品番 (品名)	S C 4 2 7	
光源	LDA4L-G-E17/Z40E/S/W/2 x1	440.0 l m
管理番号	K0157700(0)DB1	
BZ分類	BZ9	

器具効率	92%	天井	80%				70%				50%				30%				0%				
	上方光束		57%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
	下方光束		35%	壁	10%				10%				10%				10%				0%		
室指数	照明率 (X0.01)																				ZCM		
保守率	良	0.63	0.6	0.56	0.6	40	29	22	17	36	26	20	15	28	21	16	12	21	16	12	9	4	
	中	0.6	0.6	0.56	0.6	48	37	29	24	43	33	27	22	34	26	21	17	25	20	16	13	6	
	否	0.56	0.6	0.56	0.6	53	43	35	30	48	39	32	27	38	31	26	22	28	23	19	16	8	
下方投影面積 等価発光面積	c m ²	1.25	1.5	2.0	2.5	58	48	41	35	52	44	37	32	41	35	30	26	31	27	23	20	10	
		1.5	2.0	2.5	3.0	62	53	46	40	56	48	42	36	44	38	33	29	34	29	26	23	12	
		2.0	2.5	3.0	4.0	67	59	53	47	60	54	48	43	48	43	39	35	37	33	30	27	14	
取付高さ	器具間隔最大限		H m	0.00H m	0.00H m	2.5	70	63	57	52	64	57	52	48	51	46	42	39	39	36	33	30	17
	横方向 (A)	縦方向 (B)				3.0	73	66	61	56	66	60	56	51	53	49	45	42	41	38	35	32	18
H m	0.00H m	0.00H m	4.0	76	71	66	62	69	64	60	57	55	52	49	46	43	40	38	36	21			
			5.0	78	73	69	66	71	67	63	60	57	54	52	49	45	42	40	38	23			
			7.0	80	77	73	70	73	70	67	65	59	57	55	53	47	45	43	42	25			
10.0	82	79	77	75	75	73	70	68	61	59	58	56	48	47	46	44	27						

