

屋内照明器具特性

品番 (品名)	S C 4 2 8	
光源	LDA3 L - E17 / C / W ×1	280.0 l m
管理番号	K0158275 (0) DB 1	
B Z 分類	B Z 1 0	

器具効率	85 %	天井	80 %					70 %					50 %					30 %					0 %		
	上方光束		49 %	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		36 %	壁	10 %					10 %					10 %					10 %					0 %
室指数	照明率 (X0.01)																							Z C M	
保守率	良	0.63	0.6	0.6	0.56	0.6	3.6	2.5	1.8	1.4	3.2	2.3	1.7	1.2	2.5	1.8	1.3	9	1.9	1.3	1.0	7	2		
	中	0.6	0.6	0.6	0.6	0.6	4.3	3.2	2.5	2.0	3.8	2.9	2.2	1.8	3.0	2.3	1.8	1.4	2.3	1.7	1.3	1.0	4		
	否	0.56	0.56	0.56	0.56	0.56	1.0	4.8	3.7	3.0	2.4	4.3	3.4	2.7	2.2	3.4	2.7	2.2	1.8	2.6	2.0	1.6	1.3	6	
下方投影面積	c m ²		1.25	5.2	4.2	3.5	3.0	4.7	3.8	3.2	2.7	3.7	3.1	2.6	2.2	2.8	2.3	1.9	1.6	1.6	1.6	1.6	1.6	8	
	等価発光面積	c m ²		1.5	5.6	4.7	4.0	3.4	5.0	4.2	3.6	3.1	4.0	3.4	2.9	2.5	3.0	2.6	2.2	1.9	1.9	1.9	1.9	1.9	9
取付高さ	器具間隔最大限		2.5	6.3	5.6	5.0	4.5	5.8	5.1	4.6	4.1	4.6	4.2	3.7	3.4	3.6	3.2	2.9	2.6	2.6	2.6	2.6	2.6	14	
	横方向 (A)	縦方向 (B)	3.0	6.6	5.9	5.4	4.9	6.0	5.4	4.9	4.5	4.8	4.4	4.0	3.7	3.8	3.4	3.1	2.9	2.9	2.9	2.9	2.9	16	
H m	0.00H m	0.00H m	4.0	6.9	6.3	5.9	5.4	6.3	5.8	5.4	5.0	5.1	4.7	4.4	4.1	4.0	3.7	3.5	3.2	3.2	3.2	3.2	3.2	19	
			5.0	7.1	6.6	6.2	5.8	6.5	6.0	5.7	5.3	5.3	5.0	4.7	4.4	4.2	3.9	3.7	3.5	3.5	3.5	3.5	3.5	21	
			7.0	7.3	7.0	6.6	6.3	6.7	6.4	6.1	5.8	5.5	5.2	5.0	4.8	4.4	4.2	4.0	3.8	3.8	3.8	3.8	3.8	24	
			10.0	7.5	7.2	7.0	6.7	6.9	6.6	6.4	6.2	5.7	5.5	5.3	5.1	4.5	4.4	4.3	4.1	4.1	4.1	4.1	4.1	26	

